


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:220.66V I:0.0453A P:9.0628W PF:0.9059 Freq:50.01Hz Lamp Flux:886.812x1 lm		
NAME: DL9415-WHTC10C03	TYPE:	WEIGHT:
SPEC.: white RA80 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 85mm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 97.85 lm/W			
MODEL	2835 16 4000K	I _{max} (cd)	1155	S/MH(C0/180)	0.94
NOMINAL POWER(W)	9	LOR(%)	100.0	S/MH(C90/270)	0.83
RATED VOLTAGE(V)	220-240	TOTAL FLUX(lm)	886.81	η UP, DN(C0-180)	0.0, 48.2
NOMINAL FLUX(lm)	886.812	CIE CLASS	DIRECT	η UP, DN(C180-360)	0.0, 51.8
LAMPS INSIDE	1	η up(%)	0.0	CIBSE SHR NOM	0.75
TEST VOLTAGE(V)	220	η down(%)	100.0	CIBSE SHR MAX	0.85

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT: lx)



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2024-01-24

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 7.450m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	1038	1052	1072	1125	1132	1131	1106	1069	0- 10	107.1	107.1	12.1,12.1
20	727.3	762.0	848.4	951.3	987.6	955.1	882.7	787.8	10- 20	277.9	385.0	43.4,43.4
30	284.3	331.8	450.5	596.3	666.3	607.6	460.6	337.2	20- 30	307.2	692.3	78.1,78.1
40	39.89	47.46	75.76	123.5	156.8	125.7	76.00	49.34	30- 40	157.4	849.7	95.8,95.8
50	6.577	6.368	7.618	12.72	16.72	10.42	6.616	6.518	40- 50	26.67	876.4	98.8,98.8
60	5.085	4.363	3.136	2.306	2.087	2.469	3.477	4.674	50- 60	4.355	880.7	99.3,99.3
70	4.320	3.533	2.255	1.394	1.181	1.547	2.574	3.856	60- 70	2.942	883.7	99.6,99.6
80	2.732	2.214	1.372	0.8307	0.6710	0.9449	1.643	2.491	70- 80	2.302	886.0	99.9,99.9
90	0.0193	0.0154	0	0	0	0	0	0	80- 90	0.8550	886.8	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT: lm		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:
 Test Date:2024-01-24

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
 Humidity:65.0%
 Test Distance:7.450m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:220.66V I:0.0453A P:9.0628W PF:0.9059 Freq:50.01Hz Lamp Flux:886.812x1 lm		
NAME: DL9415-WHTC10C03	TYPE:	WEIGHT:
SPEC.: white RA80 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 85mm	Shielding Angle:



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	2601	1394
80	2775	1393
75	2600	1290
70	2228	1163
65	1923	1104
60	1794	1106
55	1716	1129
50	1805	2090
45	3278	6363


C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2024-01-24

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 7.450m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.66V I:0.0453A P:9.0628W PF:0.9059 Freq:50.01Hz Lamp Flux:886.812x1 lm		
NAME: DL9415-WHTC10C03	TYPE:	WEIGHT:
SPEC.: white RA80 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 85mm	Shielding Angle:

ρ_{CC}	80%			70%			50%			30%			10%			0
ρ_W	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	Coefficients of Utilization(CU)															
	RCR:Room Cavity Ratio															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1.0	1.11	1.09	1.06	1.09	1.07	1.05	1.05	1.03	1.02	1.01	.99	.99	.98	.97	.96	.94
2.0	1.04	.99	.97	1.02	.99	.96	.99	.96	.93	.96	.94	.92	.93	.91	.90	.88
3.0	.97	.92	.89	.96	.91	.88	.93	.90	.87	.91	.88	.85	.89	.86	.84	.82
4.0	.91	.86	.82	.90	.85	.82	.88	.84	.81	.86	.83	.80	.84	.81	.79	.77
5.0	.86	.80	.76	.85	.80	.76	.83	.79	.75	.82	.78	.75	.80	.77	.74	.73
6.0	.81	.75	.71	.80	.75	.71	.79	.74	.71	.77	.73	.70	.76	.72	.70	.68
7.0	.77	.71	.67	.76	.70	.67	.75	.70	.66	.73	.69	.66	.72	.69	.66	.64
8.0	.72	.67	.63	.72	.66	.63	.71	.66	.62	.70	.65	.62	.69	.65	.62	.61
9.0	.69	.63	.59	.68	.63	.59	.67	.62	.59	.66	.62	.59	.66	.62	.59	.57
10.0	.65	.60	.56	.65	.60	.56	.64	.59	.56	.63	.59	.56	.63	.58	.55	.54



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2024-01-24

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 7.450m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:220.66V I:0.0453A P:9.0628W PF:0.9059 Freq:50.01Hz Lamp Flux:886.812x1 lm					
NAME: DL9415-WHTC10C03			TYPE:		WEIGHT:
SPEC.: white RA80 3000K+5700K			DIM.:		SERIAL No.:
MFR.:			SUR.: 85mm		Shielding Angle:

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.172	.098	.031	.166	.094	.030	.153	.088	.028	.141	.082	.026	.131	.076	.024	
2.0	.164	.090	.028	.158	.087	.027	.148	.082	.026	.138	.077	.024	.129	.073	.023	
3.0	.156	.083	.025	.151	.081	.024	.142	.077	.023	.134	.073	.022	.126	.070	.022	
4.0	.148	.077	.023	.144	.075	.022	.136	.072	.022	.129	.069	.021	.122	.066	.020	
5.0	.141	.072	.021	.137	.071	.021	.131	.068	.020	.124	.066	.020	.119	.063	.019	
6.0	.135	.067	.019	.131	.066	.019	.126	.064	.019	.120	.062	.018	.115	.061	.018	
7.0	.129	.064	.018	.126	.063	.018	.121	.061	.018	.116	.059	.017	.111	.058	.017	
8.0	.123	.060	.017	.121	.060	.017	.116	.058	.017	.112	.057	.016	.108	.055	.016	
9.0	.118	.057	.016	.116	.057	.016	.112	.055	.016	.108	.054	.016	.104	.053	.015	
10.0	.114	.055	.015	.112	.054	.015	.108	.053	.015	.104	.052	.015	.101	.051	.015	

ρcc	80%			70%			50%			30%			10%			0
ρw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.171	.157	.145	.146	.135	.125	.100	.093	.086	.058	.054	.050	.018	.017	.016	
2.0	.155	.133	.113	.133	.114	.098	.091	.079	.068	.053	.046	.040	.017	.015	.013	
3.0	.142	.114	.090	.122	.098	.078	.084	.068	.055	.048	.040	.032	.016	.013	.011	
4.0	.132	.099	.073	.113	.085	.064	.078	.059	.045	.045	.035	.027	.014	.011	.009	
5.0	.123	.087	.060	.106	.075	.053	.073	.053	.037	.042	.031	.022	.014	.010	.007	
6.0	.115	.078	.051	.099	.067	.044	.068	.047	.031	.040	.028	.019	.013	.009	.006	
7.0	.109	.070	.043	.094	.061	.037	.065	.043	.026	.038	.025	.016	.012	.008	.005	
8.0	.103	.064	.037	.089	.055	.032	.061	.039	.023	.036	.023	.014	.012	.008	.004	
9.0	.098	.059	.032	.085	.051	.028	.059	.036	.020	.034	.021	.012	.011	.007	.004	
10.0	.094	.054	.028	.081	.047	.024	.056	.033	.017	.033	.020	.010	.011	.006	.003	

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:
 Test Date:2024-01-24

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
 Humidity:65.0%
 Test Distance:7.450m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.66V I:0.0453A P:9.0628W PF:0.9059 Freq:50.01Hz Lamp Flux:886.812x1 lm											
NAME: DL9415-WHTC10C03						TYPE:			WEIGHT:		
SPEC.: white RA80 3000K+5700K						DIM.:			SERIAL No.:		
MFR.:						SUR.: 85mm			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	3H	13.1	14.0	13.3	14.1	14.3	15.7	16.6	15.9	16.8	16.9
	4H	13.2	14.0	13.4	14.2	14.4	15.6	16.4	15.8	16.6	16.8
	6H	13.3	14.1	13.6	14.3	14.5	15.5	16.3	15.8	16.5	16.7
	8H	13.5	14.2	13.8	14.5	14.7	15.5	16.2	15.8	16.4	16.7
	12H	13.6	14.3	13.9	14.5	14.8	15.4	16.2	15.8	16.4	16.7
	12H	13.6	14.3	13.9	14.6	14.8	15.4	16.1	15.7	16.4	16.6
4H	2H	12.9	13.7	13.2	13.9	14.1	15.5	16.2	15.7	16.5	16.7
	3H	13.1	13.8	13.4	14.0	14.3	15.4	16.0	15.7	16.3	16.6
	4H	13.3	14.0	13.7	14.2	14.6	15.3	16.0	15.7	16.3	16.6
	6H	13.7	14.2	14.0	14.5	14.9	15.3	15.9	15.7	16.2	16.6
	8H	13.8	14.3	14.2	14.7	15.0	15.3	15.8	15.7	16.2	16.5
	12H	13.9	14.4	14.3	14.7	15.1	15.3	15.8	15.7	16.1	16.5
8H	4H	13.3	13.8	13.7	14.2	14.6	15.3	15.8	15.7	16.1	16.5
	6H	13.8	14.2	14.2	14.6	15.0	15.3	15.7	15.7	16.1	16.5
	8H	14.0	14.4	14.4	14.8	15.2	15.3	15.7	15.8	16.1	16.6
	12H	14.2	14.5	14.6	14.9	15.4	15.3	15.6	15.8	16.1	16.6
12H	4H	13.3	13.8	13.7	14.1	14.5	15.2	15.7	15.7	16.1	16.5
	6H	13.8	14.1	14.2	14.6	15.0	15.3	15.7	15.7	16.1	16.5
	8H	14.0	14.3	14.5	14.8	15.2	15.3	15.6	15.8	16.1	16.6
Variations with the observer position at spacings(CIE Pub.117):											
S = 1.0H	+ 2.2 / - 1.7					+ 4.3 / - 4.9					
1.5H	+ 4.2 / - 1.7					+ 6.8 / - 4.8					
2.0H	+ 0.6 / - 0.2					+ 3.7 / - 0.9					

CIE Pub.117, 886.8 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -0.4)
Area: 0.00567 m2

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2024-01-24

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:220.66V I:0.0453A P:9.0628W PF:0.9059 Freq:50.01Hz Lamp Flux:886.812x1 lm		
NAME: DL9415-WHTC10C03	TYPE:	WEIGHT:
SPEC.: white RA80 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 85mm	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	89	83	79	88	83	79	88	82	79	76
0.80	96	91	87	96	90	87	94	90	87	83
1.00	100	95	92	99	95	91	98	94	91	87
1.25	104	99	96	103	99	95	101	97	95	91
1.50	107	102	99	105	101	99	103	100	97	93
2.00	109	105	102	108	104	101	105	102	100	95
2.50	111	107	104	109	106	103	106	103	101	96
3.00	112	109	106	110	107	105	107	105	103	97
4.00	114	111	109	112	110	108	108	107	105	98
5.00	115	113	111	113	111	110	109	108	107	99
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:
 Test Date:2024-01-24

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
 Humidity:65.0%
 Test Distance:7.450m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:220.66V I:0.0453A P:9.0628W PF:0.9059 Freq:50.01Hz Lamp Flux:886.812x1 lm		
NAME: DL9415-WHTC10C03	TYPE:	WEIGHT:
SPEC.: white RA80 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 85mm	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2024-01-24

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

AAI Figure

Test:U:220.66V I:0.0453A P:9.0628W PF:0.9059 Freq:50.01Hz Lamp Flux:886.812x1 lm		
NAME: DL9415-WHTC10C03	TYPE:	WEIGHT:
SPEC.: white RA80 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 85mm	Shielding Angle:




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25DEG
 Operators:
 Test Date: 2024-01-24

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE G0-2000B_V1 SYSTEM V2.00.428
 Humidity: 65.0%
 Test Distance: 7.450m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM

Test:U:220.66V I:0.0453A P:9.0628W PF:0.9059 Freq:50.01Hz Lamp Flux:886.812x1 lm		
NAME: DL9415-WHTC10C03	TYPE:	WEIGHT:
SPEC.: white RA80 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 85mm	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2024-01-24

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 7.450m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:220.66V I:0.0453A P:9.0628W PF:0.9059 Freq:50.01Hz Lamp Flux:886.812x1 lm		
NAME: DL9415-WHTC10C03	TYPE:	WEIGHT:
SPEC.: white RA80 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 85mm	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	1279
L_0~180(75)av	1629
L_0~180(85)av	1631
L_90~270(65)av	1180
L_90~270(75)av	1393
L_90~270(85)av	1562
L_45(65)av	1226
L_45(75)av	1516
L_45(85)av	1624

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2024-01-24

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25DEG
 Operators:
 Test Date: 2024-01-24

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE G0-2000B_V1 SYSTEM V2.00.428
 Humidity: 65.0%
 Test Distance: 7.450m [K=1.0000]
 Remarks:

```

Range: 0 - 90DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

```