


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:220.63V I:0.0896A P:17.722W PF:0.8963 Freq:50.01Hz Lamp Flux:1568.69x1 lm		
NAME: DD1810M-BKTC2010C02	TYPE:	WEIGHT:
SPEC.: black RA90 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 88mm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 88.52 lm/W			
MODEL	TB15111204 4000K	I _{max} (cd)	1960	S/MH(C0/180)	0.79
NOMINAL POWER(W)	20	LOR(%)	100.0	S/MH(C90/270)	0.87
RATED VOLTAGE(V)	220-240	TOTAL FLUX(lm)	1568.7	η UP, DN(C0-180)	0.0, 50.3
NOMINAL FLUX(lm)	1568.69	CIE CLASS	DIRECT	η UP, DN(C180-360)	0.0, 49.7
LAMPS INSIDE	1	η up(%)	0.0	CIBSE SHR NOM	0.75
TEST VOLTAGE(V)	220	η down(%)	100.0	CIBSE SHR MAX	0.90

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2023-12-25

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 7.450m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	1903	1870	1823	1790	1784	1807	1851	1900	0- 10	180.9	180.9	11.5, 11.5
20	1598	1543	1420	1328	1324	1374	1461	1565	10- 20	467.9	648.8	41.4, 41.4
30	1084	1012	851.8	714.4	672.7	739.5	926.2	1063	20- 30	542.2	1191	75.9, 75.9
40	289.4	204.1	113.2	84.28	78.57	87.75	125.5	259.7	30- 40	293.7	1485	94.6, 94.6
50	39.59	34.24	28.87	25.48	24.31	25.31	29.43	37.06	40- 50	51.84	1537	98, 98
60	16.89	15.85	13.73	12.07	11.44	12.13	14.09	16.32	50- 60	18.66	1555	99.1, 99.1
70	7.246	7.095	5.748	4.912	4.627	5.048	6.123	7.439	60- 70	9.563	1565	99.8, 99.8
80	1.807	2.155	0.5169	0.7868	0.5672	0.8107	0.5915	2.141	70- 80	3.662	1568	100, 100
90	0.0347	0.0579	0.0618	0.0656	0.0116	0.0116	0	0	80- 90	0.2548	1569	100, 100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25DEG
 Operators:
 Test Date: 2023-12-25

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE G0-2000B_V1 SYSTEM V2.00.428
 Humidity: 65.0%
 Test Distance: 7.450m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:220.63V I:0.0896A P:17.722W PF:0.8963 Freq:50.01Hz Lamp Flux:1568.69x1 lm		
NAME: DD1810M-BKTC2010C02	TYPE:	WEIGHT:
SPEC.: black RA90 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 88mm	Shielding Angle:



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	66	80
80	1712	490
75	2663	1919
70	3485	2764
65	4447	3624
60	5555	4516
55	6958	5656
50	10131	7388
45	19649	11153

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2023-12-25

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 7.450m [K=1.0000]
Remarks:

```

Range: 0 - 90DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

```

WEC AND CCEC

Test:U:220.63V I:0.0896A P:17.722W PF:0.8963 Freq:50.01Hz Lamp Flux:1568.69x1 lm					
NAME: DD1810M-BKTC2010C02			TYPE:		WEIGHT:
SPEC.: black RA90 3000K+5700K			DIM.:		SERIAL No.:
MFR.:			SUR.: 88mm		Shielding Angle:

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.175	.099	.031	.168	.096	.030	.155	.089	.028	.144	.083	.027	.133	.077	.025	
2.0	.167	.091	.028	.161	.089	.027	.151	.084	.026	.141	.079	.025	.132	.075	.024	
3.0	.159	.084	.025	.154	.082	.025	.145	.079	.024	.137	.075	.023	.129	.071	.022	
4.0	.151	.079	.023	.147	.077	.023	.139	.074	.022	.132	.071	.021	.125	.068	.021	
5.0	.144	.073	.021	.140	.072	.021	.134	.070	.020	.127	.067	.020	.121	.065	.020	
6.0	.137	.069	.020	.134	.068	.020	.128	.066	.019	.123	.064	.019	.118	.062	.018	
7.0	.131	.065	.018	.129	.064	.018	.123	.062	.018	.118	.061	.018	.114	.059	.017	
8.0	.126	.061	.017	.123	.061	.017	.119	.059	.017	.114	.058	.017	.110	.057	.016	
9.0	.121	.058	.016	.118	.058	.016	.114	.056	.016	.110	.055	.016	.107	.054	.016	
10.0	.116	.056	.015	.114	.055	.015	.110	.054	.015	.106	.053	.015	.103	.052	.015	

ρcc	80%			70%			50%			30%			10%			0
ρw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.171	.157	.145	.146	.135	.125	.100	.093	.086	.058	.054	.050	.018	.017	.016	
2.0	.156	.133	.113	.133	.114	.098	.091	.079	.068	.053	.046	.040	.017	.015	.013	
3.0	.143	.114	.090	.123	.098	.078	.084	.068	.055	.049	.040	.032	.016	.013	.011	
4.0	.133	.099	.073	.114	.085	.063	.078	.059	.045	.045	.035	.026	.015	.011	.009	
5.0	.124	.087	.060	.106	.075	.052	.073	.053	.037	.042	.031	.022	.014	.010	.007	
6.0	.116	.078	.050	.100	.067	.044	.069	.047	.031	.040	.028	.018	.013	.009	.006	
7.0	.110	.070	.042	.095	.061	.037	.065	.043	.026	.038	.025	.016	.012	.008	.005	
8.0	.104	.064	.036	.090	.056	.032	.062	.039	.022	.036	.023	.013	.012	.008	.004	
9.0	.099	.059	.031	.085	.051	.027	.059	.036	.020	.034	.021	.012	.011	.007	.004	
10.0	.095	.054	.028	.082	.047	.024	.057	.033	.017	.033	.020	.010	.011	.006	.003	

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2023-12-25

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.63V I:0.0896A P:17.722W PF:0.8963 Freq:50.01Hz Lamp Flux:1568.69x1 lm											
NAME: DD1810M-BKTC2010C02						TYPE:			WEIGHT:		
SPEC.: black RA90 3000K+5700K						DIM.:			SERIAL No.:		
MFR.:						SUR.: 88mm			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H		19.6	20.5	19.8	20.7	20.8	17.6	18.5	17.8	18.7	18.8
	3H	19.4	20.3	19.7	20.5	20.7	17.5	18.3	17.7	18.5	18.7
	4H	19.4	20.2	19.6	20.4	20.6	17.4	18.2	17.7	18.4	18.7
	6H	19.3	20.0	19.6	20.3	20.5	17.3	18.1	17.6	18.3	18.6
	8H	19.2	20.0	19.6	20.2	20.5	17.3	18.0	17.6	18.3	18.5
	12H	19.2	19.9	19.5	20.2	20.4	17.2	17.9	17.6	18.2	18.5
4H	2H	19.3	20.1	19.6	20.4	20.6	17.4	18.2	17.7	18.4	18.6
	3H	19.2	19.9	19.5	20.2	20.5	17.3	18.0	17.6	18.3	18.5
	4H	19.2	19.8	19.5	20.1	20.4	17.2	17.9	17.6	18.2	18.5
	6H	19.1	19.6	19.5	20.0	20.3	17.1	17.7	17.5	18.0	18.4
	8H	19.0	19.5	19.4	19.9	20.3	17.1	17.6	17.5	18.0	18.3
	12H	19.0	19.4	19.4	19.8	20.2	17.0	17.5	17.5	17.9	18.3
8H	4H	19.0	19.5	19.4	19.9	20.3	17.1	17.6	17.5	18.0	18.3
	6H	18.9	19.4	19.4	19.8	20.2	17.0	17.5	17.5	17.8	18.3
	8H	18.9	19.3	19.3	19.7	20.1	17.0	17.3	17.4	17.8	18.2
	12H	18.8	19.2	19.3	19.6	20.1	16.9	17.2	17.4	17.7	18.1
12H	4H	19.0	19.4	19.4	19.8	20.2	17.1	17.5	17.5	17.9	18.3
	6H	18.9	19.3	19.3	19.7	20.1	17.0	17.4	17.4	17.8	18.2
	8H	18.8	19.2	19.3	19.6	20.1	16.9	17.2	17.4	17.7	18.2
Variations with the observer position at spacings(CIE Pub.117):											
S = 1.0H	+ 4.1 / - 8.2					+ 2.8 / - 5.5					
1.5H	+ 6.6 / - 7.2					+ 5.0 / - 4.5					
2.0H	+ 4.4 / - 2.2					+ 2.5 / - 1.7					

CIE Pub.117, 1569 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 1.6)
Area: 0.00608 m2

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2023-12-25

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:220.63V I:0.0896A P:17.722W PF:0.8963 Freq:50.01Hz Lamp Flux:1568.69x1 lm		
NAME: DD1810M-BKTC2010C02	TYPE:	WEIGHT:
SPEC.: black RA90 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 88mm	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	88	82	78	88	82	78	87	81	78	75
0.80	96	90	86	95	89	86	94	89	86	82
1.00	100	94	91	99	94	91	97	94	90	86
1.25	104	99	95	103	98	95	101	97	94	90
1.50	106	102	98	105	101	98	103	99	97	93
2.00	109	105	102	107	104	101	105	102	99	94
2.50	110	107	104	109	106	103	106	103	101	95
3.00	112	109	106	110	107	105	107	105	103	96
4.00	114	111	109	112	110	108	108	107	105	98
5.00	115	113	111	113	111	110	109	108	107	99
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2023-12-25

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:220.63V I:0.0896A P:17.722W PF:0.8963 Freq:50.01Hz Lamp Flux:1568.69x1 lm		
NAME: DD1810M-BKTC2010C02	TYPE:	WEIGHT:
SPEC.: black RA90 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 88mm	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2023-12-25

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

AAI Figure

Test:U:220.63V I:0.0896A P:17.722W PF:0.8963 Freq:50.01Hz Lamp Flux:1568.69x1 lm		
NAME: DD1810M-BKTC2010C02	TYPE:	WEIGHT:
SPEC.: black RA90 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 88mm	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2023-12-25

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:220.63V I:0.0896A P:17.722W PF:0.8963 Freq:50.01Hz Lamp Flux:1568.69x1 lm		
NAME: DD1810M-BKTC2010C02	TYPE:	WEIGHT:
SPEC.: black RA90 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 88mm	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2023-12-25

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 7.450m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:220.63V I:0.0896A P:17.722W PF:0.8963 Freq:50.01Hz Lamp Flux:1568.69x1 lm		
NAME: DD1810M-BKTC2010C02	TYPE:	WEIGHT:
SPEC.: black RA90 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 88mm	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	3683
L_0~180(75)av	2104
L_0~180(85)av	44
L_90~270(65)av	3678
L_90~270(75)av	1965
L_90~270(85)av	40
L_45(65)av	3705
L_45(75)av	2302
L_45(85)av	46

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2023-12-25

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25DEG
 Operators:
 Test Date: 2023-12-25

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE G0-2000B_V1 SYSTEM V2.00.428
 Humidity: 65.0%
 Test Distance: 7.450m [K=1.0000]
 Remarks:

```

Range: 0 - 90DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

```