


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:230.50V I:0.0508A P:11.250W PF:0.9609 Freq:49.99Hz Lamp Flux:917.961x1 lm		
NAME: 3A-DL9660-WHTC13C01 13W	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 38mm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 81.60 lm/W			
MODEL	5000K	I _{max} (cd)	1112	S/MH(C0/180)	0.87
NOMINAL POWER(W)	13	LOR(%)	100.0	S/MH(C90/270)	0.87
RATED VOLTAGE(V)	220-240	TOTAL FLUX(lm)	917.96	η UP, DN(C0-180)	0.0, 44.9
NOMINAL FLUX(lm)	917.961	CIE CLASS	DIRECT	η UP, DN(C180-360)	0.0, 55.1
LAMPS INSIDE	1	η up(%)	0.0	CIBSE SHR NOM	0.75
TEST VOLTAGE(V)	220	η down(%)	100.0	CIBSE SHR MAX	0.85

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT: lx)



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2024-09-03

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 7.450m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	994.9	981.2	995.1	1034	1077	1082	1081	1051	0- 10	102.5	102.5	11.2,11.2
20	691.7	670.1	688.5	761.3	850.7	879.9	854.3	778.0	10- 20	257.3	359.7	39.2,39.2
30	357.9	339.1	350.3	399.7	489.2	526.2	500.8	422.8	20- 30	270.2	629.9	68.6,68.6
40	125.0	110.3	122.3	154.0	205.0	230.9	210.4	167.5	30- 40	174.5	804.4	87.6,87.6
50	28.75	24.50	30.06	40.21	60.85	61.76	57.52	42.71	40- 50	71.10	875.5	95.4,95.4
60	11.85	11.39	12.64	13.97	17.99	18.06	17.43	14.28	50- 60	21.97	897.5	97.8,97.8
70	7.084	6.682	7.222	8.057	9.136	9.308	9.174	8.195	60- 70	10.80	908.3	98.9,98.9
80	4.977	4.931	5.224	5.405	5.584	5.518	5.372	5.156	70- 80	6.763	915.0	99.7,99.7
90	0.1158	0.1120	0.1120	0.1158	0.0077	0.0077	0.0039	0	80- 90	2.919	918.0	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT: lm		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:
 Test Date:2024-09-03

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE G0-2000A_V1 SYSTEM V2.00.428
 Humidity:65.0%
 Test Distance:7.450m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:230.50V I:0.0508A P:11.250W PF:0.9609 Freq:49.99Hz Lamp Flux:917.961x1 lm		
NAME: 3A-DL9660-WHTC13C01 13W	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 38mm	Shielding Angle:



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	1426	1654
80	25363	26622
75	18965	19572
70	18329	18688
65	19225	20079
60	20970	22363
55	26152	28090
50	39580	41389
45	76584	75457


C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2024-09-03

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 7.450m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:230.50V I:0.0508A P:11.250W PF:0.9609 Freq:49.99Hz Lamp Flux:917.961x1 lm		
NAME: 3A-DL9660-WHTC13C01 13W	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 38mm	Shielding Angle:

ρ_{CC}	80%			70%			50%			30%			10%			0
ρ_W	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	Coefficients of Utilization(CU)															
	RCR:Room Cavity Ratio															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	.00
1.0	1.10	1.08	1.05	1.08	1.06	1.04	1.04	1.02	1.00	1.00	.99	.97	.97	.96	.95	.93
2.0	1.02	.98	.94	1.00	.97	.93	.97	.94	.91	.94	.92	.89	.91	.89	.87	.86
3.0	.95	.90	.86	.94	.89	.85	.91	.87	.84	.88	.85	.82	.86	.83	.81	.79
4.0	.89	.83	.78	.87	.82	.78	.85	.81	.77	.83	.79	.76	.81	.78	.75	.74
5.0	.83	.77	.72	.82	.76	.72	.80	.75	.71	.78	.74	.71	.77	.73	.70	.69
6.0	.78	.71	.67	.77	.71	.67	.75	.70	.66	.74	.69	.66	.73	.69	.65	.64
7.0	.73	.67	.62	.72	.66	.62	.71	.66	.62	.70	.65	.62	.69	.64	.61	.60
8.0	.69	.63	.58	.68	.62	.58	.67	.62	.58	.66	.61	.58	.65	.61	.58	.56
9.0	.65	.59	.55	.64	.59	.55	.63	.58	.55	.63	.58	.54	.62	.57	.54	.53
10.0	.61	.56	.52	.61	.55	.52	.60	.55	.51	.59	.55	.51	.59	.54	.51	.50



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2024-09-03

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 7.450m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:230.50V I:0.0508A P:11.250W PF:0.9609 Freq:49.99Hz Lamp Flux:917.961x1 lm									
NAME: 3A-DL9660-WHTC13C01 13W					TYPE:			WEIGHT:	
SPEC.:					DIM.:			SERIAL No.:	
MFR.:					SUR.: 38mm			Shielding Angle:	

ρ_{cc}	80%			70%			50%			30%			10%			0	
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
ρ_{fc}	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)										
0.0																	
1.0	.188	.107	.034	.182	.104	.033	.169	.097	.031	.157	.091	.029	.147	.085	.027		
2.0	.179	.098	.030	.174	.096	.029	.163	.091	.028	.153	.086	.027	.144	.081	.026		
3.0	.170	.091	.027	.165	.088	.027	.156	.085	.026	.148	.081	.025	.140	.077	.024		
4.0	.161	.084	.025	.157	.082	.024	.149	.079	.024	.142	.076	.023	.135	.073	.022		
5.0	.153	.078	.023	.149	.077	.022	.143	.074	.022	.136	.072	.021	.130	.070	.021		
6.0	.146	.073	.021	.142	.072	.021	.136	.070	.020	.131	.068	.020	.125	.066	.020		
7.0	.139	.069	.019	.136	.068	.019	.130	.066	.019	.125	.064	.019	.121	.063	.018		
8.0	.132	.065	.018	.130	.064	.018	.125	.062	.018	.121	.061	.018	.116	.060	.017		
9.0	.127	.061	.017	.124	.061	.017	.120	.059	.017	.116	.058	.017	.112	.057	.016		
10.0	.121	.058	.016	.119	.058	.016	.115	.056	.016	.112	.055	.016	.108	.054	.016		

ρcc	80%			70%			50%			30%			10%			0
ρw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.172	.157	.144	.147	.135	.124	.101	.093	.086	.058	.054	.050	.019	.017	.016	
2.0	.157	.132	.112	.135	.114	.096	.092	.079	.067	.053	.046	.039	.017	.015	.013	
3.0	.145	.114	.088	.125	.098	.077	.085	.068	.054	.049	.040	.032	.016	.013	.010	
4.0	.135	.099	.071	.116	.086	.062	.080	.060	.044	.046	.035	.026	.015	.011	.008	
5.0	.127	.088	.059	.109	.076	.051	.075	.053	.036	.043	.031	.021	.014	.010	.007	
6.0	.119	.078	.049	.102	.068	.043	.071	.047	.030	.041	.028	.018	.013	.009	.006	
7.0	.113	.071	.041	.097	.061	.036	.067	.043	.026	.039	.025	.015	.013	.008	.005	
8.0	.107	.065	.035	.092	.056	.031	.064	.039	.022	.037	.023	.013	.012	.008	.004	
9.0	.102	.059	.031	.088	.052	.027	.061	.036	.019	.035	.021	.011	.011	.007	.004	
10.0	.097	.055	.027	.084	.048	.024	.058	.034	.017	.034	.020	.010	.011	.007	.003	

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:
 Test Date:2024-09-03

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE G0-2000A_V1 SYSTEM V2.00.428
 Humidity:65.0%
 Test Distance:7.450m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:230.50V I:0.0508A P:11.250W PF:0.9609 Freq:49.99Hz Lamp Flux:917.961x1 lm										
NAME: 3A-DL9660-WHTC13C01 13W					TYPE:			WEIGHT:		
SPEC.:					DIM.:			SERIAL No.:		
MFR.:					SUR.: 38mm			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	22.4	23.3	22.6	23.5	23.7	22.2	23.2	22.5	23.4	23.6
3H	22.4	23.3	22.7	23.5	23.7	22.3	23.2	22.6	23.4	23.6
4H	22.5	23.4	22.8	23.6	23.8	22.4	23.3	22.7	23.5	23.7
6H	22.7	23.5	23.0	23.7	24.0	22.6	23.4	22.9	23.7	23.9
8H	22.8	23.6	23.1	23.8	24.1	22.8	23.6	23.1	23.8	24.1
12H	22.8	23.5	23.1	23.8	24.1	22.8	23.5	23.1	23.8	24.1
4H 2H	22.2	23.1	22.5	23.3	23.5	22.1	23.0	22.4	23.2	23.4
3H	22.4	23.1	22.7	23.4	23.7	22.3	23.0	22.6	23.3	23.6
4H	22.6	23.2	22.9	23.5	23.8	22.5	23.1	22.8	23.4	23.8
6H	22.9	23.5	23.2	23.8	24.1	22.8	23.4	23.2	23.8	24.1
8H	23.1	23.7	23.5	24.0	24.4	23.1	23.7	23.5	24.0	24.4
12H	23.1	23.6	23.5	24.0	24.4	23.1	23.6	23.5	24.0	24.4
8H 4H	22.6	23.1	23.0	23.5	23.8	22.5	23.0	22.9	23.4	23.8
6H	23.1	23.5	23.5	23.9	24.3	23.0	23.5	23.5	23.9	24.3
8H	23.4	23.8	23.8	24.2	24.6	23.4	23.8	23.9	24.2	24.7
12H	23.4	23.7	23.8	24.1	24.6	23.4	23.8	23.9	24.2	24.7
12H 4H	22.6	23.1	23.0	23.4	23.8	22.5	23.0	22.9	23.4	23.8
6H	23.1	23.5	23.6	23.9	24.4	23.1	23.5	23.5	23.9	24.3
8H	23.4	23.8	23.9	24.2	24.7	23.5	23.8	23.9	24.3	24.7
Variations with the observer position at spacings(CIE Pub.117):										
S = 1.0H	+ 2.0 / - 2.3					+ 1.9 / - 2.1				
1.5H	+ 3.8 / - 2.3					+ 3.6 / - 2.1				
2.0H	+ 3.0 / - 0.9					+ 2.8 / - 0.8				

CIE Pub.117, 918.0 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -0.3)
Area: 0.00113 m2

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2024-09-03

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE G0-2000A_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:230.50V I:0.0508A P:11.250W PF:0.9609 Freq:49.99Hz Lamp Flux:917.961x1 lm		
NAME: 3A-DL9660-WHTC13C01 13W	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 38mm	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	84	77	73	83	77	73	82	76	72	69
0.80	92	85	81	91	85	81	90	84	81	77
1.00	97	91	87	96	90	86	94	90	86	82
1.25	101	95	92	100	95	91	98	94	90	86
1.50	104	99	95	103	98	95	101	97	94	89
2.00	107	103	99	106	102	98	103	100	97	91
2.50	109	105	102	107	104	101	104	101	99	93
3.00	111	107	104	109	106	103	106	103	101	94
4.00	113	110	107	111	108	106	107	105	103	96
5.00	114	112	110	112	110	108	108	107	105	97
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2024-09-03

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE G0-2000A_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:230.50V I:0.0508A P:11.250W PF:0.9609 Freq:49.99Hz Lamp Flux:917.961x1 lm		
NAME: 3A-DL9660-WHTC13C01 13W	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 38mm	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2024-09-03

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE G0-2000A_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

AAI Figure

Test:U:230.50V I:0.0508A P:11.250W PF:0.9609 Freq:49.99Hz Lamp Flux:917.961x1 lm		
NAME: 3A-DL9660-WBTC13C01 13W	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 38mm	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2024-09-03

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE G0-2000A_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:230.50V I:0.0508A P:11.250W PF:0.9609 Freq:49.99Hz Lamp Flux:917.961x1 lm		
NAME: 3A-DL9660-WHTC13C01 13W	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 38mm	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2024-09-03

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 7.450m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:230.50V I:0.0508A P:11.250W PF:0.9609 Freq:49.99Hz Lamp Flux:917.961x1 lm		
NAME: 3A-DL9660-WHTC13C01 13W	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 38mm	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	22550
L_0~180(75)av	21356
L_0~180(85)av	25317
L_90~270(65)av	22901
L_90~270(75)av	21639
L_90~270(85)av	23707
L_45(65)av	22215
L_45(75)av	21263
L_45(85)av	29008

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2024-09-03

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE G0-2000A_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2024-09-03

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 7.450m [K=1.0000]
Remarks:

```

Range: 0 - 90DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

```