


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:230.77V I:0.0491A P:10.411W PF:0.9198 Freq:49.99Hz Lamp Flux:766.195x1 lm		
NAME: DL1560-WH5C10S01	TYPE:	WEIGHT:
SPEC.: white RA80 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 69mm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 73.59 lm/W
MODEL	2835 52 3000K	I _{max} (cd)	297.2	S/MH(C0/180)	1.20	
NOMINAL POWER(W)	10	LOR(%)	100.0	S/MH(C90/270)	1.21	
RATED VOLTAGE(V)	220-240	TOTAL FLUX(lm)	766.20	η UP, DN(C0-180)	0.0, 49.6	
NOMINAL FLUX(lm)	766.195	CIE CLASS	DIRECT	η UP, DN(C180-360)	0.0, 50.4	
LAMPS INSIDE	1	η up(%)	0.0	CIBSE SHR NOM	1.25	
TEST VOLTAGE(V)	220	η down(%)	100.0	CIBSE SHR MAX	1.35	

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT: lx)



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2024-05-11

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 7.450m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	289.7	286.5	284.1	282.3	289.6	287.2	285.4	283.9	0- 10	27.61	27.61	3.6,3.6
20	268.8	265.5	263.2	261.3	268.7	267.0	265.8	264.2	10- 20	77.99	105.6	13.8,13.8
30	237.9	234.8	232.2	230.4	238.2	237.0	236.2	234.9	20- 30	115.5	221.1	28.9,28.9
40	200.2	197.2	194.7	193.4	200.4	199.6	199.1	198.0	30- 40	135.5	356.7	46.6,46.6
50	158.3	155.6	153.4	152.5	158.6	158.3	157.9	157.1	40- 50	136.7	493.3	64.4,64.4
60	114.3	112.1	110.3	109.8	114.7	114.7	114.6	113.9	50- 60	120.3	613.7	80.1,80.1
70	69.76	67.84	66.49	66.34	70.05	70.41	70.58	70.14	60- 70	89.84	703.5	91.8,91.8
80	25.74	26.66	26.18	26.46	26.49	28.93	29.48	29.34	70- 80	50.17	753.7	98.4,98.4
90	0.4362	0.4362	0.3938	0.4324	0.2818	0.3783	0.5057	0.4941	80- 90	12.50	766.2	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT: lm		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:
 Test Date:2024-05-11

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 γ Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
 Humidity:65.0%
 Test Distance:7.450m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:230.77V I:0.0491A P:10.411W PF:0.9198 Freq:49.99Hz Lamp Flux:766.195x1 lm		
NAME: DL1560-WH5C10S01	TYPE:	WEIGHT:
SPEC.: white RA80 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 69mm	Shielding Angle:



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	25352	30594
80	39636	40313
75	48510	46926
70	54537	51977
65	58228	55868
60	61120	58996
55	63587	61512
50	65854	63812
45	67923	65955


C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2024-05-11

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 7.450m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:230.77V I:0.0491A P:10.411W PF:0.9198 Freq:49.99Hz Lamp Flux:766.195x1 lm		
NAME: DL1560-WH5C10S01	TYPE:	WEIGHT:
SPEC.: white RA80 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 69mm	Shielding Angle:

ρ_{CC}	80%			70%			50%			30%			10%			0
ρ_W	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)									
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1.0	1.04	1.00	.96	1.02	.98	.95	.98	.95	.92	.94	.91	.89	.90	.88	.86	.84
2.0	.91	.84	.79	.89	.83	.78	.86	.80	.76	.82	.78	.74	.79	.76	.73	.70
3.0	.80	.72	.66	.79	.71	.65	.76	.69	.64	.73	.67	.63	.70	.66	.62	.60
4.0	.71	.62	.56	.70	.62	.55	.67	.60	.55	.65	.59	.54	.63	.58	.53	.51
5.0	.64	.55	.48	.63	.54	.48	.60	.53	.47	.58	.52	.47	.57	.51	.46	.44
6.0	.57	.49	.42	.56	.48	.42	.55	.47	.42	.53	.46	.41	.51	.46	.41	.39
7.0	.52	.43	.37	.51	.43	.37	.50	.42	.37	.48	.42	.37	.47	.41	.36	.34
8.0	.48	.39	.33	.47	.39	.33	.46	.38	.33	.44	.38	.33	.43	.37	.33	.31
9.0	.44	.36	.30	.43	.35	.30	.42	.35	.30	.41	.34	.30	.40	.34	.30	.28
10.0	.40	.33	.27	.40	.32	.27	.39	.32	.27	.38	.32	.27	.37	.31	.27	.25



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2024-05-11

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 7.450m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:230.77V I:0.0491A P:10.411W PF:0.9198 Freq:49.99Hz Lamp Flux:766.195x1 lm					
NAME: DL1560-WH5C10S01			TYPE:		WEIGHT:
SPEC.: white RA80 3000K+5700K			DIM.:		SERIAL No.:
MFR.:			SUR.: 69mm		Shielding Angle:

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.302	.172	.054	.295	.168	.053	.282	.162	.052	.269	.155	.050	.258	.150	.048	
2.0	.285	.156	.048	.279	.154	.047	.267	.149	.046	.257	.144	.045	.247	.140	.044	
3.0	.265	.141	.042	.259	.139	.042	.249	.135	.041	.239	.131	.040	.231	.128	.040	
4.0	.245	.127	.037	.240	.126	.037	.231	.122	.037	.222	.119	.036	.215	.117	.036	
5.0	.227	.116	.033	.222	.114	.033	.214	.112	.033	.207	.109	.032	.200	.107	.032	
6.0	.211	.106	.030	.207	.104	.030	.200	.102	.030	.193	.100	.029	.187	.098	.029	
7.0	.196	.097	.027	.193	.096	.027	.186	.094	.027	.180	.092	.027	.175	.091	.027	
8.0	.183	.090	.025	.180	.089	.025	.175	.087	.025	.169	.086	.025	.164	.084	.025	
9.0	.172	.083	.023	.169	.083	.023	.164	.081	.023	.159	.080	.023	.155	.079	.023	
10.0	.162	.078	.022	.159	.077	.021	.155	.076	.021	.150	.075	.021	.146	.074	.021	

ρcc	80%			70%			50%			30%			10%			0	
ρw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
ρfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)										
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020		
1.0	.180	.156	.135	.154	.134	.116	.105	.092	.080	.061	.053	.047	.019	.017	.015		
2.0	.171	.132	.099	.147	.114	.085	.101	.079	.060	.058	.046	.035	.019	.015	.011		
3.0	.163	.114	.075	.140	.099	.065	.096	.068	.046	.056	.040	.027	.018	.013	.009		
4.0	.156	.101	.059	.134	.087	.051	.092	.061	.036	.053	.036	.021	.017	.012	.007		
5.0	.148	.090	.048	.127	.078	.042	.088	.055	.029	.051	.032	.017	.016	.010	.006		
6.0	.141	.082	.040	.121	.071	.034	.084	.050	.024	.049	.029	.014	.016	.010	.005		
7.0	.134	.075	.034	.116	.065	.029	.080	.046	.021	.046	.027	.012	.015	.009	.004		
8.0	.128	.069	.029	.110	.060	.025	.076	.042	.018	.044	.025	.011	.014	.008	.004		
9.0	.122	.064	.025	.105	.056	.022	.073	.039	.016	.042	.023	.009	.014	.008	.003		
10.0	.116	.060	.023	.100	.052	.020	.070	.037	.014	.041	.022	.008	.013	.007	.003		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:
 Test Date:2024-05-11

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
 Humidity:65.0%
 Test Distance:7.450m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:230.77V I:0.0491A P:10.411W PF:0.9198 Freq:49.99Hz Lamp Flux:766.195x1 lm										
NAME: DL1560-WH5C10S01					TYPE:			WEIGHT:		
SPEC.: white RA80 3000K+5700K					DIM.:			SERIAL No.:		
MFR.:					SUR.: 69mm			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	28.2	29.6	28.4	29.9	30.1	28.0	29.5	28.3	29.7	29.9
3H	29.6	31.0	29.9	31.2	31.5	29.4	30.8	29.7	31.0	31.3
4H	30.1	31.5	30.5	31.7	32.0	30.0	31.3	30.3	31.5	31.8
6H	30.5	31.7	30.8	32.0	32.3	30.3	31.6	30.6	31.8	32.1
8H	30.6	31.7	30.9	32.0	32.3	30.4	31.6	30.8	31.9	32.2
12H	30.6	31.7	30.9	32.0	32.3	30.5	31.6	30.8	31.9	32.2
4H 2H	28.7	30.0	29.0	30.3	30.5	28.6	29.9	28.9	30.2	30.4
3H	30.3	31.5	30.7	31.8	32.1	30.2	31.3	30.5	31.6	31.9
4H	31.0	32.1	31.4	32.4	32.7	30.8	31.9	31.2	32.2	32.6
6H	31.4	32.4	31.8	32.7	33.1	31.3	32.3	31.7	32.6	33.0
8H	31.6	32.4	32.0	32.8	33.2	31.5	32.3	31.9	32.7	33.1
12H	31.6	32.4	32.0	32.8	33.2	31.6	32.3	32.0	32.7	33.1
8H 4H	31.2	32.1	31.6	32.5	32.9	31.1	32.0	31.5	32.3	32.7
6H	31.8	32.5	32.2	32.9	33.4	31.7	32.4	32.1	32.8	33.3
8H	32.0	32.6	32.4	33.0	33.5	31.9	32.6	32.4	33.0	33.4
12H	32.1	32.6	32.5	33.1	33.5	32.1	32.6	32.5	33.1	33.5
12H 4H	31.2	32.0	31.7	32.4	32.8	31.1	31.9	31.5	32.3	32.7
6H	31.8	32.5	32.3	32.9	33.4	31.7	32.4	32.2	32.8	33.3
8H	32.1	32.6	32.5	33.0	33.5	32.0	32.5	32.5	33.0	33.5
Variations with the observer position at spacings(CIE Pub.117):										
S = 1.0H	+ 0.2 / - 0.2					+ 0.2 / - 0.2				
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3				
2.0H	+ 0.2 / - 0.3					+ 0.2 / - 0.3				

CIE Pub.117, 766.2 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -0.9)
Area: 0.00374 m2

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2024-05-11

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:230.77V I:0.0491A P:10.411W PF:0.9198 Freq:49.99Hz Lamp Flux:766.195x1 lm		
NAME: DL1560-WH5C10S01	TYPE:	WEIGHT:
SPEC.: white RA80 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 69mm	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	59	47	40	58	47	40	57	46	40	34
0.80	69	57	50	68	57	50	66	56	49	43
1.00	77	66	59	76	66	59	74	67	58	51
1.25	84	74	67	83	73	66	80	72	66	58
1.50	89	79	72	87	78	72	84	77	71	63
2.00	96	87	81	94	86	80	90	84	79	71
2.50	99	92	86	97	90	85	94	88	83	75
3.00	103	96	91	101	94	90	97	92	87	79
4.00	107	101	97	104	99	95	100	96	93	84
5.00	109	104	100	107	102	99	102	99	96	87
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25DEG
 Operators:
 Test Date: 2024-05-11

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE G0-2000B_V1 SYSTEM V2.00.428
 Humidity: 65.0%
 Test Distance: 7.450m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:230.77V I:0.0491A P:10.411W PF:0.9198 Freq:49.99Hz Lamp Flux:766.195x1 lm		
NAME: DL1560-WH5C10S01	TYPE:	WEIGHT:
SPEC.: white RA80 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 69mm	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2024-05-11

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

AAI Figure

Test:U:230.77V I:0.0491A P:10.411W PF:0.9198 Freq:49.99Hz Lamp Flux:766.195x1 lm		
NAME: DL1560-WH5C10S01	TYPE:	WEIGHT:
SPEC.: white RA80 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 69mm	Shielding Angle:

Flux out:519.2 lm




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25DEG
 Operators:
 Test Date: 2024-05-11

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE G0-2000B_V1 SYSTEM V2.00.428
 Humidity: 65.0%
 Test Distance: 7.450m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM

Test:U:230.77V I:0.0491A P:10.411W PF:0.9198 Freq:49.99Hz Lamp Flux:766.195x1 lm		
NAME: DL1560-WH5C10S01	TYPE:	WEIGHT:
SPEC.: white RA80 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 69mm	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2024-05-11

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 7.450m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:230.77V I:0.0491A P:10.411W PF:0.9198 Freq:49.99Hz Lamp Flux:766.195x1 lm		
NAME: DL1560-WH5C10S01	TYPE:	WEIGHT:
SPEC.: white RA80 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 69mm	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	58317
L_0~180(75)av	48962
L_0~180(85)av	26154
L_90~270(65)av	57207
L_90~270(75)av	48878
L_90~270(85)av	34540
L_45(65)av	57300
L_45(75)av	49056
L_45(85)av	34105

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2024-05-11

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2024-05-11

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 7.450m [K=1.0000]
Remarks:

```

Range: 0 - 90DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

```