


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:230.66V I:0.0462A P:9.4740W PF:0.8899 Freq:49.99Hz Lamp Flux:805.817x1 lm		
NAME: DL1561-WH3C10S01	TYPE:	WEIGHT:
SPEC.: white RA80 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 69mm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 85.06 lm/W
MODEL	2835 52 4000K	I _{max} (cd)	348.1	S/MH(C0/180)	1.21	
NOMINAL POWER(W)	10	LOR(%)	100.0	S/MH(C90/270)	1.22	
RATED VOLTAGE(V)	220-240	TOTAL FLUX(lm)	805.82	η UP, DN(C0-180)	0.0, 49.8	
NOMINAL FLUX(lm)	805.817	CIE CLASS	DIRECT	η UP, DN(C180-360)	0.0, 50.2	
LAMPS INSIDE	1	η up(%)	0.0	CIBSE SHR NOM	0.75	
TEST VOLTAGE(V)	220	η down(%)	100.0	CIBSE SHR MAX	0.85	

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT: lx)



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2024-10-21

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 7.450m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	339.4	336.3	333.9	331.9	340.0	337.5	335.5	333.1	0- 10	28.38	28.38	3.52, 3.52
20	316.3	313.0	310.7	309.3	316.7	314.8	312.8	311.1	10- 20	80.43	108.8	13.5, 13.5
30	282.0	278.5	276.5	275.0	282.2	280.1	279.0	278.0	20- 30	119.8	228.6	28.4, 28.4
40	238.6	236.2	233.6	232.0	239.8	237.7	237.4	235.8	30- 40	141.4	369.9	45.9, 45.9
50	190.1	187.4	185.8	184.2	190.9	189.6	189.0	188.7	40- 50	143.6	513.5	63.7, 63.7
60	138.4	136.3	134.4	133.6	139.1	138.0	138.0	137.9	50- 60	127.3	640.8	79.5, 79.5
70	85.51	84.35	82.70	82.11	85.98	85.60	85.61	85.78	60- 70	95.88	736.7	91.4, 91.4
80	32.47	35.64	34.59	33.75	32.71	36.48	36.58	36.19	70- 80	54.68	791.4	98.2, 98.2
90	0.5289	0.5327	0.4864	0.5482	0.3359	0.3397	0.2973	0.5173	80- 90	14.44	805.8	100, 100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT: lm		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25DEG
 Operators:
 Test Date: 2024-10-21

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.428
 Humidity: 65.0%
 Test Distance: 7.450m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:230.66V I:0.0462A P:9.4740W PF:0.8899 Freq:49.99Hz Lamp Flux:805.817x1 lm		
NAME: DL1561-WH3C10S01	TYPE:	WEIGHT:
SPEC.: white RA80 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 69mm	Shielding Angle:



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	32820	44079
80	49999	53261
75	59963	59662
70	66852	64656
65	70759	68782
60	73999	71867
55	76660	74742
50	79090	77274
45	81240	79463


C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2024-10-21

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 7.450m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:230.66V I:0.0462A P:9.4740W PF:0.8899 Freq:49.99Hz Lamp Flux:805.817x1 lm		
NAME: DL1561-WH3C10S01	TYPE:	WEIGHT:
SPEC.: white RA80 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 69mm	Shielding Angle:

ρ_{CC}	80%			70%			50%			30%			10%			0
ρ_W	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	Coefficients of Utilization(CU)															
RCR:Room Cavity Ratio																
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1.0	1.04	.90	.96	1.02	.98	.94	.98	.94	.91	.94	.91	.89	.90	.88	.86	.84
2.0	.91	.84	.78	.89	.83	.77	.85	.80	.76	.82	.78	.74	.79	.75	.72	.70
3.0	.80	.72	.65	.78	.71	.65	.75	.69	.64	.73	.67	.62	.70	.65	.61	.59
4.0	.71	.62	.55	.69	.61	.55	.67	.60	.54	.65	.58	.53	.62	.57	.53	.51
5.0	.63	.54	.48	.62	.54	.48	.60	.53	.47	.58	.52	.46	.56	.51	.46	.44
6.0	.57	.48	.42	.56	.48	.42	.54	.47	.41	.53	.46	.41	.51	.45	.40	.38
7.0	.52	.43	.37	.51	.43	.37	.49	.42	.37	.48	.41	.36	.47	.41	.36	.34
8.0	.47	.39	.33	.47	.39	.33	.45	.38	.33	.44	.37	.32	.43	.37	.32	.30
9.0	.43	.35	.30	.43	.35	.30	.42	.35	.29	.41	.34	.29	.40	.34	.29	.27
10.0	.40	.32	.27	.40	.32	.27	.39	.32	.27	.38	.31	.27	.37	.31	.27	.25



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2024-10-21

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 7.450m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:230.66V I:0.0462A P:9.4740W PF:0.8899 Freq:49.99Hz Lamp Flux:805.817x1 lm					
NAME: DL1561-WH3C10S01			TYPE:		WEIGHT:
SPEC.: white RA80 3000K+5700K			DIM.:		SERIAL No.:
MFR.:			SUR.: 69mm		Shielding Angle:

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.306	.174	.055	.298	.170	.054	.285	.164	.052	.273	.157	.051	.262	.152	.049	
2.0	.288	.158	.048	.282	.155	.048	.270	.150	.047	.259	.145	.046	.249	.141	.044	
3.0	.267	.142	.043	.261	.140	.042	.251	.136	.041	.241	.132	.041	.233	.129	.040	
4.0	.246	.128	.038	.242	.126	.037	.232	.123	.037	.224	.120	.036	.216	.117	.036	
5.0	.228	.116	.034	.224	.115	.033	.216	.112	.033	.208	.110	.033	.201	.107	.032	
6.0	.212	.106	.030	.208	.105	.030	.201	.103	.030	.194	.101	.030	.188	.099	.029	
7.0	.197	.097	.028	.194	.097	.028	.187	.095	.027	.181	.093	.027	.176	.091	.027	
8.0	.184	.090	.025	.181	.089	.025	.175	.088	.025	.170	.086	.025	.165	.085	.025	
9.0	.173	.084	.023	.170	.083	.023	.165	.081	.023	.160	.080	.023	.155	.079	.023	
10.0	.162	.078	.022	.160	.077	.022	.155	.076	.021	.151	.075	.021	.147	.074	.021	

ρ _{CC}	80%			70%			50%			30%			10%			0
ρ _W	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.180	.156	.135	.154	.134	.116	.105	.092	.080	.061	.053	.047	.019	.017	.015	
2.0	.172	.132	.098	.147	.114	.085	.101	.079	.059	.058	.046	.035	.019	.015	.011	
3.0	.164	.114	.075	.140	.099	.065	.096	.068	.045	.056	.040	.027	.018	.013	.009	
4.0	.156	.101	.059	.134	.087	.051	.092	.061	.036	.053	.036	.021	.017	.012	.007	
5.0	.149	.090	.048	.128	.078	.041	.088	.055	.029	.051	.032	.017	.016	.010	.006	
6.0	.142	.082	.039	.122	.071	.034	.084	.050	.024	.049	.029	.014	.016	.010	.005	
7.0	.135	.075	.033	.116	.065	.029	.080	.046	.021	.047	.027	.012	.015	.009	.004	
8.0	.128	.069	.029	.110	.060	.025	.076	.042	.018	.044	.025	.011	.014	.008	.004	
9.0	.122	.064	.025	.105	.056	.022	.073	.039	.016	.043	.023	.009	.014	.008	.003	
10.0	.117	.060	.023	.101	.052	.020	.070	.037	.014	.041	.022	.008	.013	.007	.003	

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:
 Test Date:2024-10-21

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE G0-2000A_V1 SYSTEM V2.00.428
 Humidity:65.0%
 Test Distance:7.450m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:230.66V I:0.0462A P:9.4740W PF:0.8899 Freq:49.99Hz Lamp Flux:805.817x1 lm											
NAME: DL1561-WH3C10S01						TYPE:			WEIGHT:		
SPEC.: white RA80 3000K+5700K						DIM.:			SERIAL No.:		
MFR.:						SUR.: 69mm			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	29.1	30.6	29.4	30.8	31.0	29.0	30.5	29.3	30.7	30.9	
	3H	30.6	32.0	30.9	32.2	32.5	30.5	31.9	30.8	32.1	32.3
	4H	31.2	32.5	31.5	32.7	33.0	31.0	32.4	31.4	32.6	32.9
	6H	31.5	32.8	31.9	33.1	33.3	31.4	32.7	31.8	33.0	33.2
	8H	31.6	32.8	32.0	33.1	33.4	31.6	32.8	31.9	33.1	33.4
	12H	31.6	32.8	32.0	33.1	33.4	31.6	32.8	32.0	33.1	33.4
4H	2H	29.7	31.0	30.0	31.3	31.5	29.6	30.9	29.9	31.2	31.4
	3H	31.4	32.5	31.7	32.8	33.1	31.3	32.4	31.6	32.7	33.0
	4H	32.1	33.1	32.4	33.4	33.8	32.0	33.0	32.3	33.3	33.7
	6H	32.6	33.5	33.0	33.8	34.2	32.5	33.4	32.9	33.8	34.2
	8H	32.7	33.6	33.1	33.9	34.3	32.7	33.6	33.1	33.9	34.3
	12H	32.7	33.6	33.2	33.9	34.3	32.8	33.6	33.2	34.0	34.4
8H	4H	32.3	33.2	32.7	33.6	33.9	32.2	33.1	32.6	33.5	33.9
	6H	33.0	33.7	33.4	34.1	34.5	32.9	33.6	33.4	34.0	34.5
	8H	33.2	33.8	33.6	34.2	34.7	33.2	33.8	33.6	34.2	34.7
	12H	33.3	33.8	33.8	34.3	34.8	33.4	33.9	33.8	34.4	34.8
12H	4H	32.3	33.1	32.8	33.5	33.9	32.2	33.0	32.7	33.4	33.8
	6H	33.0	33.7	33.5	34.1	34.5	33.0	33.6	33.4	34.0	34.5
	8H	33.3	33.8	33.7	34.3	34.7	33.3	33.8	33.7	34.3	34.8
Variations with the observer position at spacings(CIE Pub.117):											
S = 1.0H	+ 0.2 / - 0.2					+ 0.2 / - 0.2					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.2 / - 0.2					+ 0.2 / - 0.3					

CIE Pub.117, 805.8 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -0.8)
Area: 0.00374 m2

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2024-10-21

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE G0-2000A_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:230.66V I:0.0462A P:9.4740W PF:0.8899 Freq:49.99Hz Lamp Flux:805.817x1 lm		
NAME: DL1561-WH3C10S01	TYPE:	WEIGHT:
SPEC.: white RA80 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 69mm	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	58	47	40	58	47	40	56	46	40	33
0.80	68	57	50	67	56	49	65	56	49	42
1.00	77	66	58	75	65	58	73	66	58	51
1.25	84	73	66	82	73	66	80	71	65	58
1.50	89	79	72	87	78	71	84	76	70	63
2.00	95	87	81	94	86	80	90	84	78	71
2.50	99	92	86	97	90	85	93	88	83	75
3.00	103	96	90	100	94	89	96	91	87	79
4.00	106	101	96	104	99	95	100	96	92	83
5.00	109	104	100	106	102	99	102	99	95	86
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2024-10-21

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE G0-2000A_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:230.66V I:0.0462A P:9.4740W PF:0.8899 Freq:49.99Hz Lamp Flux:805.817x1 lm		
NAME: DL1561-WH3C10S01	TYPE:	WEIGHT:
SPEC.: white RA80 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 69mm	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2024-10-21

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 7.450m [K=1.0000]
Remarks:

AAI Figure

Test:U:230.66V I:0.0462A P:9.4740W PF:0.8899 Freq:49.99Hz Lamp Flux:805.817x1 lm		
NAME: DL1561-WH3C10S01	TYPE:	WEIGHT:
SPEC.: white RA80 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 69mm	Shielding Angle:

Flux out:554.2 lm




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25DEG
 Operators:
 Test Date: 2024-10-21

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.428
 Humidity: 65.0%
 Test Distance: 7.450m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM

Test:U:230.66V I:0.0462A P:9.4740W PF:0.8899 Freq:49.99Hz Lamp Flux:805.817x1 lm		
NAME: DL1561-WH3C10S01	TYPE:	WEIGHT:
SPEC.: white RA80 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 69mm	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2024-10-21

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 7.450m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:230.66V I:0.0462A P:9.4740W PF:0.8899 Freq:49.99Hz Lamp Flux:805.817x1 lm		
NAME: DL1561-WH3C10S01	TYPE:	WEIGHT:
SPEC.: white RA80 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 69mm	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	70952
L_0~180(75)av	60181
L_0~180(85)av	33028
L_90~270(65)av	69744
L_90~270(75)av	60986
L_90~270(85)av	46081
L_45(65)av	69826
L_45(75)av	61163
L_45(85)av	45677

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:
 Test Date:2024-10-21

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE G0-2000A_V1 SYSTEM V2.00.428
 Humidity:65.0%
 Test Distance:7.450m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2024-10-21

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 7.450m [K=1.0000]
Remarks:

```

Range: 0 - 90DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

```