



Cut-out: Ø88mm-90mm

FEATURES

- Die-casting aluminum heatsink+PC replaceable frame achieve cost-down downlight solution with good heat dissipation.
- IP54 waterproof, wet environment feasible.
- High efficiency, up to 105.7lm/W.
- 3-year guarantee.
- Multi-functional design with single colour, COB tri-colour, SMD tri-colour, SMD dim-to-warm as options.
- External driver and dimming capability suits triac dimmers including OPUS, Clipsal, HPM, Niko, Lumeo Domus, Lumeo Eco. The driver with SAA, RCM and CE certification.

Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC33-38V/210mA
Power	10W
Rated Input Current	0.045A
PF value	>0.9
THD	25%
Ingress Protection	IP54
Operating Temperature	-10-40°C
Dimmability	Triac dimmable with DIMMATE driver

Optical Data

LED Brand	Hongli SMD LED
CRI	Ra > 80
Colour temperature	3000K-4000K-5000K

Packaging

Box Dimensions	L120 x W120x H120mm
Box Net Weight	0.25Kg
Box Gross Weight	0.29Kg
Carton Dimensions	L500 x W380 x H230 mm/36 PCS
Carton Net Weight	9.0Kg
Carton Gross Weight	11.3Kg



Lens

CCT		Beam Angle	Lumen	Lumen
3000K	CRI 80+	60°	786lm	698lm
4000K		60°	921lm	781lm
5000K		60°	867lm	742lm
Reflector				