


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:230.03V I:0.1059A P:22.989W PF:0.9440 Freq:49.99Hz Lamp Flux:2490.58x1 lm		
NAME: AL5011-WHTC24S02-TS	TYPE:	WEIGHT:
SPEC.:white RA90 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.:195mm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 108.34 lm/W			
MODEL	2835 192 5700K	I _{max} (cd)	1597	S/MH(C0/180)	0.98
NOMINAL POWER(W)	24	LOR(%)	100.0	S/MH(C90/270)	1.03
RATED VOLTAGE(V)	120	TOTAL FLUX(lm)	2490.6	η UP, DN(C0-180)	0.0, 50.2
NOMINAL FLUX(lm)	2490.58	CIE CLASS	DIRECT	η UP, DN(C180-360)	0.0, 49.8
LAMPS INSIDE	1	η up(%)	0.0	CIBSE SHR NOM	1.00
TEST VOLTAGE(V)	120.0	η down(%)	100.0	CIBSE SHR MAX	1.10

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2024-07-11

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE G0-2000A_V1 SYSTEM V2.0.402
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	1560	1552	1537	1523	1523	1532	1547	1559	0- 10	149.8	149.8	6.01, 6.01
20	1388	1372	1337	1303	1300	1320	1355	1383	10- 20	410.0	559.7	22.5, 22.5
30	1074	1059	1016	971.5	966.4	989.0	1033	1069	20- 30	545.8	1105	44.4, 44.4
40	733.5	721.5	681.2	637.4	628.2	646.0	689.0	726.7	30- 40	531.3	1637	65.7, 65.7
50	383.1	376.2	353.4	310.6	300.3	320.5	360.1	378.3	40- 50	389.5	2026	81.4, 81.4
60	181.2	189.7	191.4	164.4	149.3	170.3	195.1	188.0	50- 60	222.6	2249	90.3, 90.3
70	103.6	112.8	108.5	96.48	86.96	100.2	111.4	113.0	60- 70	136.6	2385	95.8, 95.8
80	56.61	56.11	49.80	41.62	39.02	43.51	51.38	56.58	70- 80	80.40	2466	99, 99
90	3.998	2.325	0.9184	0.9646	0.4370	0.4318	0.4129	2.257	80- 90	24.70	2491	100, 100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2024-07-11

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 γ Test System: EVERFINE G0-2000A_V1 SYSTEM V2.0.402
Humidity: 65.0%
Test Distance: 7.450m [K=1.0000]
Remarks:

LUMINANCE LIMITATION CURVES

Test:U:230.03V I:0.1059A P:22.989W PF:0.9440 Freq:49.99Hz Lamp Flux:2490.58x1 lm		
NAME: AL5011-WHTC24S02-TS	TYPE:	WEIGHT:
SPEC.:white RA90 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.:195mm	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2024-07-11

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE G0-2000A_V1 SYSTEM V2.0.402
Humidity: 65.0%
Test Distance: 7.450m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:230.03V I:0.1059A P:22.989W PF:0.9440 Freq:49.99Hz Lamp Flux:2490.58x1 lm		
NAME: AL5011-WHTC24S02-TS	TYPE:	WEIGHT:
SPEC.:white RA90 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.:195mm	Shielding Angle:

ρ_{CC}	80%			70%			50%			30%			10%			0
ρ_W	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	Coefficients of Utilization(CU)															
RCR:Room Cavity Ratio																
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1.0	1.07	1.04	1.01	1.05	1.02	.99	1.01	.98	.96	.97	.95	.93	.93	.92	.90	.88
2.0	.96	.91	.86	.95	.90	.85	.91	.87	.83	.88	.85	.82	.85	.82	.80	.78
3.0	.87	.81	.75	.86	.80	.75	.83	.78	.73	.80	.76	.72	.78	.74	.71	.69
4.0	.79	.72	.66	.78	.71	.66	.76	.70	.65	.73	.68	.64	.71	.67	.63	.62
5.0	.72	.65	.59	.71	.64	.59	.69	.63	.58	.68	.62	.58	.66	.61	.57	.55
6.0	.66	.59	.53	.66	.58	.53	.64	.57	.53	.62	.57	.52	.61	.56	.52	.50
7.0	.61	.54	.48	.60	.53	.48	.59	.53	.48	.58	.52	.48	.56	.51	.47	.46
8.0	.57	.49	.44	.56	.49	.44	.55	.48	.44	.54	.48	.44	.53	.47	.43	.42
9.0	.53	.45	.41	.52	.45	.40	.51	.45	.40	.50	.44	.40	.49	.44	.40	.38
10.0	.49	.42	.37	.49	.42	.37	.48	.41	.37	.47	.41	.37	.46	.41	.37	.35



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2024-07-11

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE G0-2000A_V1 SYSTEM V2.0.402
Humidity: 65.0%
Test Distance: 7.450m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:230.03V I:0.1059A P:22.989W PF:0.9440 Freq:49.99Hz Lamp Flux:2490.58x1 lm					
NAME: AL5011-WHTC24S02-TS			TYPE:		WEIGHT:
SPEC.:white RA90 3000K+5700K			DIM.:		SERIAL No.:
MFR.:			SUR.:195mm		Shielding Angle:

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.246	.140	.044	.239	.136	.043	.226	.130	.041	.214	.123	.040	.203	.118	.038	
2.0	.234	.128	.039	.228	.126	.039	.217	.121	.037	.206	.116	.036	.197	.111	.035	
3.0	.220	.117	.035	.215	.115	.035	.205	.111	.034	.196	.107	.033	.187	.104	.032	
4.0	.206	.107	.031	.201	.105	.031	.193	.102	.031	.185	.099	.030	.178	.096	.029	
5.0	.193	.098	.029	.189	.097	.028	.182	.095	.028	.175	.092	.027	.168	.090	.027	
6.0	.182	.091	.026	.178	.090	.026	.171	.088	.026	.165	.086	.025	.159	.084	.025	
7.0	.171	.085	.024	.168	.084	.024	.162	.082	.024	.156	.080	.023	.151	.078	.023	
8.0	.162	.079	.022	.159	.078	.022	.153	.077	.022	.148	.075	.022	.144	.074	.021	
9.0	.153	.074	.021	.150	.073	.021	.146	.072	.020	.141	.071	.020	.137	.069	.020	
10.0	.145	.070	.019	.143	.069	.019	.138	.068	.019	.134	.067	.019	.130	.066	.019	

ρ _{CC}	80%			70%			50%			30%			10%			0
ρ _W	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.176	.157	.139	.150	.134	.120	.103	.093	.083	.059	.054	.048	.019	.017	.016	
2.0	.165	.132	.105	.141	.114	.091	.097	.079	.063	.056	.046	.037	.018	.015	.012	
3.0	.155	.114	.081	.133	.098	.071	.091	.068	.050	.053	.040	.029	.017	.013	.010	
4.0	.146	.100	.065	.125	.086	.056	.086	.060	.040	.050	.035	.023	.016	.011	.008	
5.0	.138	.089	.053	.119	.077	.046	.082	.054	.032	.047	.032	.019	.015	.010	.006	
6.0	.131	.080	.044	.113	.070	.038	.078	.049	.027	.045	.029	.016	.015	.009	.005	
7.0	.125	.073	.037	.107	.063	.032	.074	.045	.023	.043	.026	.014	.014	.009	.004	
8.0	.119	.067	.032	.102	.058	.028	.071	.041	.020	.041	.024	.012	.013	.008	.004	
9.0	.113	.062	.028	.098	.054	.024	.068	.038	.017	.039	.022	.010	.013	.007	.003	
10.0	.108	.058	.024	.093	.050	.021	.065	.035	.015	.038	.021	.009	.012	.007	.003	

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:
 Test Date:2024-07-11

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE G0-2000A_V1 SYSTEM V2.0.402
 Humidity:65.0%
 Test Distance:7.450m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:230.03V I:0.1059A P:22.989W PF:0.9440 Freq:49.99Hz Lamp Flux:2490.58x1 lm											
NAME: AL5011-WHTC24S02-TS						TYPE:			WEIGHT:		
SPEC.:white RA90 3000K+5700K						DIM.:			SERIAL No.:		
MFR.:						SUR.:195mm			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H		18.5	19.8	18.8	20.0	20.2	18.1	19.4	18.4	19.6	19.8
	3H	19.2	20.4	19.5	20.6	20.8	18.9	20.0	19.2	20.3	20.5
	4H	19.6	20.7	19.9	20.9	21.2	19.2	20.3	19.5	20.6	20.8
	6H	19.9	21.0	20.3	21.2	21.5	19.6	20.6	19.9	20.8	21.1
	8H	20.1	21.1	20.4	21.4	21.6	19.7	20.7	20.0	20.9	21.2
	12H	20.2	21.2	20.6	21.5	21.8	19.7	20.7	20.1	21.0	21.3
4H	2H	18.7	19.8	19.0	20.1	20.3	18.4	19.5	18.7	19.7	20.0
	3H	19.7	20.6	20.0	20.9	21.2	19.4	20.3	19.7	20.6	20.9
	4H	20.2	21.1	20.6	21.4	21.7	19.9	20.7	20.2	21.0	21.4
	6H	20.7	21.5	21.1	21.9	22.2	20.3	21.1	20.7	21.4	21.8
	8H	21.0	21.7	21.4	22.0	22.4	20.5	21.2	20.9	21.6	22.0
	12H	21.2	21.8	21.6	22.2	22.6	20.6	21.3	21.1	21.7	22.1
8H	4H	20.4	21.1	20.8	21.5	21.9	20.1	20.8	20.5	21.2	21.5
	6H	21.1	21.7	21.5	22.1	22.5	20.7	21.3	21.1	21.7	22.1
	8H	21.4	22.0	21.9	22.4	22.8	21.0	21.5	21.4	21.9	22.4
	12H	21.7	22.2	22.2	22.6	23.1	21.2	21.7	21.7	22.1	22.6
12H	4H	20.4	21.1	20.8	21.4	21.8	20.1	20.8	20.5	21.1	21.5
	6H	21.2	21.7	21.6	22.1	22.5	20.8	21.3	21.2	21.7	22.2
	8H	21.5	22.0	22.0	22.4	22.9	21.1	21.6	21.6	22.0	22.5
Variations with the observer position at spacings:											
S = 1.0H	+ 0.5 / - 0.6					+ 0.5 / - 0.6					
1.5H	+ 0.4 / - 0.5					+ 0.5 / - 0.4					
2.0H	+ 1.1 / - 0.8					+ 1.2 / - 0.6					

CIE Pub.117, 2491 lm Total Lamp Luminous Flux Correct ($8\log(F/F_0) = 3.2$)

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25DEG
 Operators:
 Test Date: 2024-07-11

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE G0-2000A_V1 SYSTEM V2.0.402
 Humidity: 65.0%
 Test Distance: 7.450m [K=1.0000]
 Remarks:

UTILIZATION FACTORS TABLE

Test:U:230.03V I:0.1059A P:22.989W PF:0.9440 Freq:49.99Hz Lamp Flux:2490.58x1 lm		
NAME: AL5011-WHTC24S02-TS	TYPE:	WEIGHT:
SPEC.:white RA90 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.:195mm	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	70	61	55	70	61	55	69	60	55	50
0.80	79	70	65	79	70	64	77	69	64	59
1.00	87	78	72	86	77	72	84	78	72	66
1.25	92	84	79	91	84	79	89	82	78	72
1.50	96	89	84	95	88	83	92	87	82	76
2.00	101	95	90	100	94	89	97	92	88	81
2.50	104	98	94	102	97	93	99	95	91	84
3.00	107	102	97	105	100	96	101	97	94	87
4.00	110	105	102	108	104	101	104	100	98	90
5.00	112	108	105	109	106	103	105	102	100	92
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2024-07-11

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 γ Test System:EVERFINE G0-2000A_V1 SYSTEM V2.0.402
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:230.03V I:0.1059A P:22.989W PF:0.9440 Freq:49.99Hz Lamp Flux:2490.58x1 lm		
NAME: AL5011-WHTC24S02-TS	TYPE:	WEIGHT:
SPEC.:white RA90 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.:195mm	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2024-07-11

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE G0-2000A_V1 SYSTEM V2.0.402
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

AAI Figure

Test:U:230.03V I:0.1059A P:22.989W PF:0.9440 Freq:49.99Hz Lamp Flux:2490.58x1 lm		
NAME: AL5011-WHTC24S02-TS	TYPE:	WEIGHT:
SPEC.:white RA90 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.:195mm	Shielding Angle:

Flux out:1486 lm




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25DEG
 Operators:
 Test Date: 2024-07-11

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE G0-2000A_V1 SYSTEM V2.0.402
 Humidity: 65.0%
 Test Distance: 7.450m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM

Test:U:230.03V I:0.1059A P:22.989W PF:0.9440 Freq:49.99Hz Lamp Flux:2490.58x1 lm		
NAME: AL5011-WHTC24S02-TS	TYPE:	WEIGHT:
SPEC.:white RA90 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.:195mm	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2024-07-11

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE G0-2000A_V1 SYSTEM V2.0.402
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:230.03V I:0.1059A P:22.989W PF:0.9440 Freq:49.99Hz Lamp Flux:2490.58x1 lm		
NAME: AL5011-WHTC24S02-TS	TYPE:	WEIGHT:
SPEC.:white RA90 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.:195mm	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	9779
L_0~180(75)av	9311
L_0~180(85)av	8166
L_90~270(65)av	11637
L_90~270(75)av	10186
L_90~270(85)av	8699
L_45(65)av	10904
L_45(75)av	9934
L_45(85)av	8437

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2024-07-11

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE G0-2000A_V1 SYSTEM V2.0.402
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2024-07-11

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE G0-2000A_V1 SYSTEM V2.0.402
Humidity: 65.0%
Test Distance: 7.450m [K=1.0000]
Remarks:

```

Range: 0 - 90DEG
Interval: 1.0DEG
Test System:EVERFINE G0-2000A_V1 SYSTEM V2.0.402
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

```