


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:220.58V I:0.0611A P:13.183W PF:0.9786 Freq:50.01Hz Lamp Flux:1129.04x1 lm		
NAME: DL2082-BKTC15C01P	TYPE:	WEIGHT:
SPEC.: black R80 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 60mm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 85.64 lm/W			
MODEL	TB15111204 5700K	I _{max} (cd)	1359	S/MH(C0/180)	0.89
NOMINAL POWER(W)	12	LOR(%)	100.0	S/MH(C90/270)	0.91
RATED VOLTAGE(V)	220-240	TOTAL FLUX(lm)	1129.0	η UP, DN(C0-180)	0.0,49.2
NOMINAL FLUX(lm)	1129.04	CIE CLASS	DIRECT	η UP, DN(C180-360)	0.0,50.8
LAMPS INSIDE	1	η up(%)	0.0	CIBSE SHR NOM	0.75
TEST VOLTAGE(V)	220	η down(%)	100.0	CIBSE SHR MAX	0.95

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2023-10-20

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	1266	1261	1259	1259	1268	1268	1269	1271	0- 10	125.7	125.7	11.1, 11.1
20	1056	1030	1031	1030	1051	1069	1082	1079	10- 20	330.9	456.6	40.4, 40.4
30	679.7	680.8	675.4	672.8	681.5	683.6	689.1	690.2	20- 30	394.1	850.7	75.3, 75.3
40	92.71	70.27	66.40	64.13	76.53	91.99	95.51	91.36	30- 40	238.9	1090	96.5, 96.5
50	14.38	14.22	14.10	14.08	14.39	14.61	14.74	14.58	40- 50	23.28	1113	98.6, 98.6
60	6.846	6.761	6.711	6.769	6.996	7.100	7.112	7.031	50- 60	9.193	1122	99.4, 99.4
70	2.725	2.694	2.690	2.763	2.873	2.915	2.911	2.857	60- 70	4.594	1127	99.8, 99.8
80	1.066	1.063	1.078	1.136	1.145	1.137	1.157	1.130	70- 80	1.869	1129	100, 100
90	0.0077	0.0077	0.0116	0.0077	0	0	0	0	80- 90	0.5043	1129	100, 100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2023-10-20

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

LUMINANCE LIMITATION CURVES

Test:U:220.58V I:0.0611A P:13.183W PF:0.9786 Freq:50.01Hz Lamp Flux:1129.04x1 lm		
NAME: DL2082-BKTC15C01P	TYPE:	WEIGHT:
SPEC.: black R80 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 60mm	Shielding Angle:



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	1851	1601
80	2170	2193
75	2185	2200
70	2815	2779
65	3732	3671
60	4838	4743
55	6210	6087
50	7906	7749
45	11525	11370


C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2023-10-20

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 7.450m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.58V I:0.0611A P:13.183W PF:0.9786 Freq:50.01Hz Lamp Flux:1129.04x1 lm		
NAME: DL2082-BKTC15C01P	TYPE:	WEIGHT:
SPEC.: black R80 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 60mm	Shielding Angle:

ρ_{CC}	80%			70%			50%			30%			10%			0
ρ_W	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1.0	1.11	1.09	1.06	1.09	1.07	1.05	1.05	1.03	1.01	1.01	.99	.98	.98	.97	.96	.94
2.0	1.04	.99	.96	1.02	.98	.95	.99	.96	.93	.96	.93	.91	.93	.91	.89	.88
3.0	.97	.92	.88	.95	.91	.87	.93	.89	.86	.90	.87	.85	.88	.86	.83	.82
4.0	.91	.85	.81	.90	.85	.81	.87	.83	.80	.85	.82	.79	.84	.81	.78	.77
5.0	.85	.80	.75	.84	.79	.75	.83	.78	.74	.81	.77	.74	.79	.76	.73	.72
6.0	.80	.74	.70	.79	.74	.70	.78	.73	.70	.77	.72	.69	.75	.72	.69	.67
7.0	.76	.70	.66	.75	.69	.66	.74	.69	.65	.72	.68	.65	.71	.67	.64	.63
8.0	.71	.66	.62	.71	.65	.61	.70	.65	.61	.69	.64	.61	.68	.64	.61	.59
9.0	.68	.62	.58	.67	.62	.58	.66	.61	.58	.65	.61	.57	.64	.60	.57	.56
10.0	.64	.58	.55	.64	.58	.55	.63	.58	.54	.62	.57	.54	.61	.57	.54	.53



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2023-10-20

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 7.450m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:220.58V I:0.0611A P:13.183W PF:0.9786 Freq:50.01Hz Lamp Flux:1129.04x1 lm					
NAME: DL2082-BKTC15C01P			TYPE:		WEIGHT:
SPEC.: black R80 3000K+5700K			DIM.:		SERIAL No.:
MFR.:			SUR.: 60mm		Shielding Angle:

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.174	.099	.031	.167	.095	.030	.155	.089	.028	.143	.083	.026	.132	.077	.025	
2.0	.166	.091	.028	.160	.088	.027	.150	.083	.026	.140	.079	.025	.131	.074	.023	
3.0	.158	.084	.025	.153	.082	.025	.144	.078	.024	.136	.075	.023	.128	.071	.022	
4.0	.151	.078	.023	.146	.077	.023	.139	.074	.022	.132	.071	.021	.125	.068	.021	
5.0	.144	.073	.021	.140	.072	.021	.133	.069	.020	.127	.067	.020	.121	.065	.019	
6.0	.137	.069	.020	.134	.068	.019	.128	.066	.019	.123	.064	.019	.117	.062	.018	
7.0	.131	.065	.018	.129	.064	.018	.123	.062	.018	.118	.061	.018	.114	.059	.017	
8.0	.126	.062	.017	.123	.061	.017	.119	.059	.017	.114	.058	.017	.110	.057	.016	
9.0	.121	.058	.016	.119	.058	.016	.114	.057	.016	.110	.055	.016	.107	.054	.016	
10.0	.116	.056	.015	.114	.055	.015	.110	.054	.015	.107	.053	.015	.103	.052	.015	

ρ _{cc}	80%			70%			50%			30%			10%			0
ρ _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.171	.157	.145	.146	.135	.125	.100	.093	.086	.058	.054	.050	.018	.017	.016	
2.0	.155	.133	.113	.133	.114	.098	.091	.079	.068	.053	.046	.040	.017	.015	.013	
3.0	.143	.114	.090	.123	.098	.078	.084	.068	.055	.049	.040	.032	.016	.013	.011	
4.0	.133	.099	.073	.114	.085	.063	.078	.059	.045	.045	.035	.026	.015	.011	.009	
5.0	.124	.087	.060	.106	.075	.052	.073	.053	.037	.042	.031	.022	.014	.010	.007	
6.0	.116	.078	.050	.100	.067	.044	.069	.047	.031	.040	.028	.018	.013	.009	.006	
7.0	.110	.070	.042	.095	.061	.037	.065	.043	.026	.038	.025	.016	.012	.008	.005	
8.0	.104	.064	.036	.090	.056	.032	.062	.039	.022	.036	.023	.013	.012	.008	.004	
9.0	.099	.059	.031	.086	.051	.027	.059	.036	.019	.035	.021	.012	.011	.007	.004	
10.0	.095	.054	.028	.082	.047	.024	.057	.033	.017	.033	.020	.010	.011	.006	.003	

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2023-10-20

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.58V I:0.0611A P:13.183W PF:0.9786 Freq:50.01Hz Lamp Flux:1129.04x1 lm											
NAME: DL2082-BKTC15C01P						TYPE:			WEIGHT:		
SPEC.: black R80 3000K+5700K						DIM.:			SERIAL No.:		
MFR.:						SUR.: 60mm			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H		20.8	21.7	21.0	21.9	22.0	20.6	21.5	20.8	21.7	21.8
	3H	20.6	21.5	20.9	21.7	21.9	20.4	21.3	20.7	21.5	21.7
	4H	20.5	21.3	20.8	21.5	21.8	20.3	21.1	20.6	21.4	21.6
	6H	20.4	21.2	20.7	21.4	21.7	20.3	21.0	20.6	21.3	21.5
	8H	20.4	21.1	20.7	21.4	21.6	20.2	20.9	20.5	21.2	21.5
	12H	20.4	21.1	20.7	21.3	21.6	20.2	20.9	20.5	21.1	21.4
4H	2H	20.5	21.3	20.8	21.5	21.8	20.3	21.1	20.6	21.4	21.6
	3H	20.4	21.1	20.7	21.3	21.6	20.2	20.9	20.5	21.1	21.4
	4H	20.3	20.9	20.6	21.2	21.5	20.1	20.7	20.4	21.0	21.3
	6H	20.2	20.7	20.6	21.1	21.4	20.0	20.6	20.4	20.9	21.2
	8H	20.2	20.7	20.5	21.0	21.4	20.0	20.5	20.4	20.8	21.2
	12H	20.1	20.6	20.5	20.9	21.3	19.9	20.4	20.3	20.8	21.2
8H	4H	20.1	20.7	20.5	21.0	21.4	20.0	20.5	20.4	20.8	21.2
	6H	20.1	20.5	20.5	20.9	21.3	19.9	20.3	20.3	20.7	21.1
	8H	20.0	20.4	20.5	20.8	21.2	19.8	20.2	20.3	20.6	21.1
	12H	20.0	20.3	20.4	20.7	21.2	19.8	20.1	20.2	20.5	21.0
12H	4H	20.1	20.6	20.5	20.9	21.3	19.9	20.4	20.3	20.7	21.1
	6H	20.0	20.4	20.4	20.8	21.2	19.8	20.2	20.3	20.6	21.1
	8H	20.0	20.3	20.4	20.7	21.2	19.8	20.1	20.2	20.5	21.0
Variations with the observer position at spacings(CIE Pub.117):											
S = 1.0H		+ 4.8 / - 8.6					+ 4.6 / - 7.7				
1.5H		+ 7.4 / - 7.5					+ 7.2 / - 6.6				
2.0H		+ 2.4 / - 1.6					+ 2.3 / - 1.6				

CIE Pub.117, 1129 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 0.4)
Area: 0.00283 m2

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2023-10-20

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:220.58V I:0.0611A P:13.183W PF:0.9786 Freq:50.01Hz Lamp Flux:1129.04x1 lm		
NAME: DL2082-BKTC15C01P	TYPE:	WEIGHT:
SPEC.: black R80 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 60mm	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	89	83	80	89	83	80	88	83	80	76
0.80	97	91	88	96	91	87	95	90	87	84
1.00	101	95	92	100	95	92	98	95	91	87
1.25	104	99	96	103	99	96	101	98	95	91
1.50	107	102	99	106	102	99	103	100	98	93
2.00	109	105	102	108	104	102	105	102	100	95
2.50	111	107	104	109	106	103	106	104	102	96
3.00	112	109	106	110	108	105	107	105	103	97
4.00	114	112	110	112	110	108	109	107	105	98
5.00	115	113	112	113	111	110	109	108	107	99
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2023-10-20

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:220.58V I:0.0611A P:13.183W PF:0.9786 Freq:50.01Hz Lamp Flux:1129.04x1 lm		
NAME: DL2082-BKTC15C01P	TYPE:	WEIGHT:
SPEC.: black R80 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 60mm	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2023-10-20

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

AAI Figure

Test:U:220.58V I:0.0611A P:13.183W PF:0.9786 Freq:50.01Hz Lamp Flux:1129.04x1 lm		
NAME: DL2082-BKTC15C01P	TYPE:	WEIGHT:
SPEC.: black R80 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 60mm	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2023-10-20

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:220.58V I:0.0611A P:13.183W PF:0.9786 Freq:50.01Hz Lamp Flux:1129.04x1 lm		
NAME: DL2082-BKTC15C01P	TYPE:	WEIGHT:
SPEC.: black R80 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 60mm	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2023-10-20

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:220.58V I:0.0611A P:13.183W PF:0.9786 Freq:50.01Hz Lamp Flux:1129.04x1 lm		
NAME: DL2082-BKTC15C01P	TYPE:	WEIGHT:
SPEC.: black R80 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 60mm	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	3801
L_0~180(75)av	2266
L_0~180(85)av	1753
L_90~270(65)av	3809
L_90~270(75)av	2298
L_90~270(85)av	1753
L_45(65)av	3800
L_45(75)av	2294
L_45(85)av	1757

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:
 Test Date:2023-10-20

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
 Humidity:65.0%
 Test Distance:7.450m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25DEG
 Operators:
 Test Date: 2023-10-20

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE G0-2000B_V1 SYSTEM V2.00.428
 Humidity: 65.0%
 Test Distance: 7.450m [K=1.0000]
 Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

```