


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:220.55V I:0.1742A P:36.997W PF:0.9632 Freq:50.01Hz Lamp Flux:3575.83x1 lm		
NAME: TH40-BKTC40C021P	TYPE:	WEIGHT:
SPEC.: black RA90 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 77mm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 96.65 lm/W			
MODEL	TB32141211 4000K	I _{max} (cd)	4373	S/MH(C0/180)	0.84
NOMINAL POWER(W)	40	LOR(%)	100.0	S/MH(C90/270)	0.85
RATED VOLTAGE(V)	220-240	TOTAL FLUX(lm)	3575.8	η UP, DN(C0-180)	0.0, 50.1
NOMINAL FLUX(lm)	3575.83	CIE CLASS	DIRECT	η UP, DN(C180-360)	0.0, 49.9
LAMPS INSIDE	1	η up(%)	0.0	CIBSE SHR NOM	0.75
TEST VOLTAGE(V)	220	η down(%)	100.0	CIBSE SHR MAX	0.90

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2023-12-21

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 7.450m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	4232	4236	4209	4195	4218	4201	4204	4218	0- 10	410.7	410.7	11.5, 11.5
20	3427	3410	3351	3330	3333	3370	3370	3423	10- 20	1082	1493	41.7, 41.7
30	1931	1918	1881	1828	1836	1860	1865	1932	20- 30	1209	2702	75.6, 75.6
40	514.4	513.4	478.2	441.7	441.8	469.0	486.1	517.9	30- 40	688.6	3390	94.8, 94.8
50	48.85	48.98	44.24	41.99	44.69	47.86	49.06	49.40	40- 50	157.6	3548	99.2, 99.2
60	8.408	8.821	8.751	8.407	8.944	9.585	8.287	8.657	50- 60	22.40	3570	99.8, 99.8
70	2.068	2.095	1.987	1.848	1.981	3.116	2.008	2.043	60- 70	4.112	3575	100, 100
80	0.5179	0.5410	0.4289	0.3324	0.2659	0.4086	0.4279	0.3777	70- 80	1.031	3576	100, 100
90	0.1969	0.2046	0.2046	0.2046	0.0309	0.0309	0.0270	0.0270	80- 90	0.2488	3576	100, 100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25DEG
 Operators:
 Test Date: 2023-12-21

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE G0-2000B_V1 SYSTEM V2.00.428
 Humidity: 65.0%
 Test Distance: 7.450m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:220.55V I:0.1742A P:36.997W PF:0.9632 Freq:50.01Hz Lamp Flux:3575.83x1 lm		
NAME: TH40-BKTC40C021P	TYPE:	WEIGHT:
SPEC.: black RA90 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 77mm	Shielding Angle:



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	695	590
80	640	530
75	649	563
70	1297	1247
65	1898	1877
60	3609	3756
55	9409	8754
50	16309	14771
45	66871	59109


C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2023-12-21

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 7.450m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.55V I:0.1742A P:36.997W PF:0.9632 Freq:50.01Hz Lamp Flux:3575.83x1 lm		
NAME: TH40-BKTC40C021P	TYPE:	WEIGHT:
SPEC.: black RA90 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 77mm	Shielding Angle:

ρ_{CC}	80%			70%			50%			30%			10%			0
ρ_W	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)									
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1.0	1.11	1.09	1.06	1.09	1.07	1.05	1.05	1.03	1.02	1.01	.99	.99	.98	.97	.96	.94
2.0	1.04	.99	.97	1.02	.98	.95	.99	.96	.93	.96	.93	.91	.93	.91	.89	.88
3.0	.97	.92	.88	.96	.91	.88	.93	.89	.86	.91	.88	.85	.88	.86	.84	.82
4.0	.91	.86	.82	.90	.85	.81	.88	.83	.80	.86	.82	.79	.84	.81	.78	.77
5.0	.85	.80	.76	.84	.79	.75	.83	.78	.75	.81	.77	.74	.80	.76	.73	.72
6.0	.80	.75	.71	.80	.74	.70	.78	.73	.70	.77	.73	.69	.75	.72	.69	.67
7.0	.76	.70	.66	.75	.70	.66	.74	.69	.65	.73	.68	.65	.72	.68	.65	.63
8.0	.72	.66	.62	.71	.66	.62	.70	.65	.61	.69	.65	.61	.68	.64	.61	.60
9.0	.68	.62	.58	.67	.62	.58	.66	.61	.58	.66	.61	.58	.65	.61	.58	.56
10.0	.64	.59	.55	.64	.58	.55	.63	.58	.55	.62	.58	.55	.62	.57	.54	.53



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2023-12-21

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 7.450m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:220.55V I:0.1742A P:36.997W PF:0.9632 Freq:50.01Hz Lamp Flux:3575.83x1 lm					
NAME: TH40-BKTC40C021P			TYPE:		WEIGHT:
SPEC.: black RA90 3000K+5700K			DIM.:		SERIAL No.:
MFR.:			SUR.: 77mm		Shielding Angle:

ρ _{CC}	80%			70%			50%			30%			10%			0	
ρ _W	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
ρ _{fc}	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)										
0.0																	
1.0	.172	.098	.031	.166	.094	.030	.153	.088	.028	.141	.082	.026	.131	.076	.024		
2.0	.165	.090	.028	.159	.088	.027	.149	.083	.026	.139	.078	.024	.130	.073	.023		
3.0	.157	.084	.025	.152	.082	.025	.143	.078	.024	.135	.074	.023	.127	.070	.022		
4.0	.150	.078	.023	.146	.076	.023	.138	.073	.022	.131	.070	.021	.124	.067	.021		
5.0	.143	.073	.021	.139	.072	.021	.133	.069	.020	.126	.067	.020	.120	.064	.019		
6.0	.137	.068	.020	.133	.067	.019	.128	.065	.019	.122	.063	.019	.117	.062	.018		
7.0	.131	.065	.018	.128	.064	.018	.123	.062	.018	.118	.060	.018	.113	.059	.017		
8.0	.125	.061	.017	.123	.060	.017	.118	.059	.017	.114	.058	.017	.110	.056	.016		
9.0	.120	.058	.016	.118	.058	.016	.114	.056	.016	.110	.055	.016	.106	.054	.016		
10.0	.116	.055	.015	.114	.055	.015	.110	.054	.015	.106	.053	.015	.103	.052	.015		

ρ _{CC}	80%			70%			50%			30%			10%			0
ρ _W	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.171	.157	.145	.146	.135	.125	.100	.093	.086	.058	.054	.050	.018	.017	.016	
2.0	.155	.133	.113	.133	.114	.098	.091	.079	.068	.053	.046	.040	.017	.015	.013	
3.0	.143	.114	.090	.122	.098	.078	.084	.068	.055	.049	.040	.032	.016	.013	.011	
4.0	.132	.099	.073	.114	.085	.064	.078	.059	.045	.045	.035	.026	.015	.011	.009	
5.0	.124	.087	.060	.106	.075	.052	.073	.053	.037	.042	.031	.022	.014	.010	.007	
6.0	.116	.078	.050	.100	.067	.044	.069	.047	.031	.040	.028	.018	.013	.009	.006	
7.0	.110	.070	.042	.094	.061	.037	.065	.043	.026	.038	.025	.016	.012	.008	.005	
8.0	.104	.064	.036	.090	.055	.032	.062	.039	.023	.036	.023	.013	.012	.008	.004	
9.0	.099	.059	.032	.085	.051	.028	.059	.036	.020	.034	.021	.012	.011	.007	.004	
10.0	.095	.054	.028	.081	.047	.024	.057	.033	.017	.033	.020	.010	.011	.006	.003	

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2023-12-21

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.55V I:0.1742A P:36.997W PF:0.9632 Freq:50.01Hz Lamp Flux:3575.83x1 lm											
NAME: TH40-BKTC40C021P					TYPE:			WEIGHT:			
SPEC.: black RA90 3000K+5700K					DIM.:			SERIAL No.:			
MFR.:					SUR.: 77mm			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H		18.8	19.7	19.0	19.8	20.0	18.5	19.4	18.7	19.6	19.8
	3H	18.6	19.4	18.8	19.6	19.8	18.3	19.2	18.6	19.4	19.6
	4H	18.5	19.3	18.8	19.5	19.7	18.2	19.0	18.5	19.3	19.5
	6H	18.4	19.2	18.7	19.4	19.6	18.2	18.9	18.5	19.1	19.4
	8H	18.4	19.1	18.7	19.3	19.6	18.1	18.8	18.4	19.1	19.3
	12H	18.3	19.0	18.6	19.3	19.6	18.1	18.8	18.4	19.0	19.3
4H	2H	18.5	19.3	18.8	19.5	19.7	18.3	19.0	18.5	19.3	19.5
	3H	18.3	19.0	18.6	19.3	19.6	18.1	18.8	18.4	19.0	19.3
	4H	18.2	18.9	18.6	19.1	19.5	18.0	18.6	18.3	18.9	19.2
	6H	18.1	18.7	18.5	19.0	19.4	17.9	18.4	18.3	18.8	19.1
	8H	18.1	18.6	18.5	18.9	19.3	17.8	18.3	18.2	18.7	19.1
	12H	18.0	18.5	18.4	18.9	19.3	17.8	18.2	18.2	18.6	19.0
8H	4H	18.1	18.6	18.5	18.9	19.3	17.8	18.3	18.2	18.7	19.1
	6H	18.0	18.4	18.4	18.8	19.2	17.7	18.1	18.2	18.5	19.0
	8H	17.9	18.3	18.4	18.7	19.1	17.7	18.0	18.1	18.5	18.9
	12H	17.9	18.2	18.3	18.6	19.1	17.6	17.9	18.1	18.4	18.8
12H	4H	18.0	18.5	18.4	18.9	19.3	17.8	18.2	18.2	18.6	19.0
	6H	17.9	18.3	18.4	18.7	19.1	17.7	18.0	18.1	18.5	18.9
	8H	17.9	18.2	18.3	18.6	19.1	17.6	17.9	18.1	18.4	18.8
Variations with the observer position at spacings(CIE Pub.117):											
S = 1.0H	+ 3.6 / -16.1					+ 3.6 / -16.0					
1.5H	+ 5.9 / -12.3					+ 6.0 / -12.1					
2.0H	+ 8.0 / -12.7					+ 7.9 / -12.1					

CIE Pub.117, 3576 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 4.4)
Area: 0.00466 m2

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2023-12-21

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:220.55V I:0.1742A P:36.997W PF:0.9632 Freq:50.01Hz Lamp Flux:3575.83x1 lm		
NAME: TH40-BKTC40C021P	TYPE:	WEIGHT:
SPEC.: black RA90 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 77mm	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	88	82	78	88	82	78	87	82	78	75
0.80	96	90	86	95	90	86	94	89	86	82
1.00	100	95	91	99	94	91	98	94	90	87
1.25	104	99	96	103	98	95	101	97	94	90
1.50	107	102	99	105	101	98	103	100	97	93
2.00	109	105	102	108	104	101	105	102	100	95
2.50	111	107	104	109	106	103	106	103	101	96
3.00	112	109	106	110	107	105	107	105	103	97
4.00	114	111	109	112	110	108	108	107	105	98
5.00	115	113	111	113	111	110	109	108	107	99
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2023-12-21

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:220.55V I:0.1742A P:36.997W PF:0.9632 Freq:50.01Hz Lamp Flux:3575.83x1 lm		
NAME: TH40-BKTC40C021P	TYPE:	WEIGHT:
SPEC.: black RA90 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 77mm	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2023-12-21

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 7.450m [K=1.0000]
Remarks:

AAI Figure

Test:U:220.55V I:0.1742A P:36.997W PF:0.9632 Freq:50.01Hz Lamp Flux:3575.83x1 lm		
NAME: TH40-BKTC40C021P	TYPE:	WEIGHT:
SPEC.: black RA90 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 77mm	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2023-12-21

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:220.55V I:0.1742A P:36.997W PF:0.9632 Freq:50.01Hz Lamp Flux:3575.83x1 lm		
NAME: TH40-BKTC40C021P	TYPE:	WEIGHT:
SPEC.: black RA90 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 77mm	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2023-12-21

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:220.55V I:0.1742A P:36.997W PF:0.9632 Freq:50.01Hz Lamp Flux:3575.83x1 lm		
NAME: TH40-BKTC40C021P	TYPE:	WEIGHT:
SPEC.: black RA90 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 77mm	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	1893
L_0~180(75)av	540
L_0~180(85)av	480
L_90~270(65)av	1879
L_90~270(75)av	579
L_90~270(85)av	513
L_45(65)av	2011
L_45(75)av	575
L_45(85)av	529

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2023-12-21

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25DEG
 Operators:
 Test Date: 2023-12-21

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE G0-2000B_V1 SYSTEM V2.00.428
 Humidity: 65.0%
 Test Distance: 7.450m [K=1.0000]
 Remarks:

```

Range: 0 - 90DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

```