


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:220.54V I:0.0603A P:12.980W PF:0.9759 Freq:50.01Hz Lamp Flux:941.49lx1 lm		
NAME: DL3017-WHTC12C02	TYPE:	WEIGHT:
SPEC.: white RA90 3000K+5000K	DIM.:	SERIAL No.:
MFR.:	SUR.: 60mm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 72.53 lm/W			
MODEL	3000K	I _{max} (cd)	3198	S/MH(C0/180)	0.43
NOMINAL POWER(W)	12	LOR(%)	100.0	S/MH(C90/270)	0.43
RATED VOLTAGE(V)	220-240	TOTAL FLUX(lm)	941.49	η UP, DN(C0-180)	0.0,49.5
NOMINAL FLUX(lm)	941.491	CIE CLASS	DIRECT	η UP, DN(C180-360)	0.0,50.5
LAMPS INSIDE	1	η up(%)	0.0	CIBSE SHR NOM	0.00
TEST VOLTAGE(V)	220	η down(%)	100.0	CIBSE SHR MAX	1.00

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2023-12-5

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	2037	1969	1941	1952	2022	2025	2052	2085	0- 10	241.6	241.6	25.7, 25.7
20	760.9	722.3	716.4	721.9	737.6	725.5	747.3	779.3	10- 20	348.6	590.1	62.7, 62.7
30	235.5	225.4	221.0	220.1	224.6	217.0	229.4	244.5	20- 30	198.2	788.3	83.7, 83.7
40	85.75	79.54	79.92	80.71	78.99	76.63	80.59	87.88	30- 40	84.51	872.8	92.7, 92.7
50	29.68	28.12	27.72	28.03	27.65	27.48	28.06	29.82	40- 50	36.88	909.7	96.6, 96.6
60	14.05	13.63	13.90	14.10	13.61	13.52	13.00	13.33	50- 60	16.50	926.2	98.4, 98.4
70	7.997	7.873	7.901	7.978	7.981	7.934	7.699	7.749	60- 70	10.98	937.2	99.5, 99.5
80	0.9251	0.8980	0.9562	1.064	1.140	1.132	1.051	0.9627	70- 80	3.982	941.2	100, 100
90	0.0270	0.0270	0.0347	0.0386	0	0	0	0	80- 90	0.3223	941.5	100, 100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25DEG
 Operators:
 Test Date: 2023-12-5

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE G0-2000B_V1 SYSTEM V2.00.428
 Humidity: 65.0%
 Test Distance: 7.450m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:220.54V I:0.0603A P:12.980W PF:0.9759 Freq:50.01Hz Lamp Flux:941.491x1 lm		
NAME: DL3017-WHTC12C02	TYPE:	WEIGHT:
SPEC.: white RA90 3000K+5000K	DIM.:	SERIAL No.:
MFR.:	SUR.: 60mm	Shielding Angle:



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	150	189
80	471	487
75	975	1015
70	2067	2043
65	2421	2399
60	2485	2457
55	2657	2577
50	4083	3813
45	6099	5629


C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2023-12-5

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 7.450m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.54V I:0.0603A P:12.980W PF:0.9759 Freq:50.01Hz Lamp Flux:941.491x1 lm		
NAME: DL3017-WHTC12C02	TYPE:	WEIGHT:
SPEC.: white RA90 3000K+5000K	DIM.:	SERIAL No.:
MFR.:	SUR.: 60mm	Shielding Angle:

ρ_{CC}	80%			70%			50%			30%			10%			0
ρ_W	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)									
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	.00
1.0	1.12	1.09	1.07	1.10	1.08	1.06	1.06	1.04	1.03	1.02	1.01	.99	.98	.98	.97	.95
2.0	1.05	1.02	.99	1.03	1.00	.98	1.00	.98	.95	.97	.95	.93	.95	.93	.91	.90
3.0	.99	.95	.92	.98	.94	.91	.95	.92	.89	.93	.90	.88	.91	.89	.87	.85
4.0	.94	.90	.86	.93	.89	.85	.91	.87	.84	.89	.86	.83	.87	.85	.83	.81
5.0	.90	.85	.81	.89	.84	.81	.87	.83	.80	.86	.82	.79	.84	.81	.79	.77
6.0	.86	.81	.77	.85	.80	.77	.84	.79	.76	.82	.79	.76	.81	.78	.75	.74
7.0	.82	.77	.74	.81	.77	.73	.80	.76	.73	.79	.75	.73	.78	.75	.72	.71
8.0	.79	.74	.70	.78	.73	.70	.77	.73	.70	.76	.72	.70	.75	.72	.69	.68
9.0	.76	.71	.68	.75	.71	.67	.74	.70	.67	.74	.70	.67	.73	.69	.67	.66
10.0	.73	.68	.65	.73	.68	.65	.72	.68	.65	.71	.67	.65	.70	.67	.64	.63



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2023-12-5

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 7.450m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:220.54V I:0.0603A P:12.980W PF:0.9759 Freq:50.01Hz Lamp Flux:941.491x1 lm					
NAME: DL3017-WHTC12C02			TYPE:		WEIGHT:
SPEC.: white RA90 3000K+5000K			DIM.:		SERIAL No.:
MFR.:			SUR.: 60mm		Shielding Angle:

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.160	.091	.029	.153	.087	.028	.141	.081	.026	.129	.074	.024	.118	.069	.022	
2.0	.151	.083	.025	.145	.080	.025	.135	.075	.023	.125	.070	.022	.116	.066	.021	
3.0	.142	.075	.023	.137	.073	.022	.128	.069	.021	.120	.066	.020	.113	.062	.019	
4.0	.133	.069	.020	.129	.068	.020	.122	.065	.019	.115	.062	.019	.109	.059	.018	
5.0	.126	.064	.019	.123	.063	.018	.116	.060	.018	.110	.058	.017	.105	.056	.017	
6.0	.119	.060	.017	.116	.059	.017	.111	.057	.017	.106	.055	.016	.101	.053	.016	
7.0	.113	.056	.016	.111	.055	.016	.106	.054	.015	.101	.052	.015	.097	.050	.015	
8.0	.108	.053	.015	.106	.052	.015	.101	.051	.014	.097	.049	.014	.093	.048	.014	
9.0	.103	.050	.014	.101	.049	.014	.097	.048	.014	.094	.047	.013	.090	.046	.013	
10.0	.099	.047	.013	.097	.047	.013	.093	.046	.013	.090	.045	.013	.087	.044	.013	

ρ_{CC}	80%			70%			50%			30%			10%			0
ρ_W	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fC}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.170	.157	.146	.145	.135	.126	.099	.093	.087	.057	.054	.051	.018	.017	.016	
2.0	.153	.133	.115	.131	.114	.099	.090	.079	.069	.052	.046	.041	.017	.015	.013	
3.0	.140	.113	.092	.120	.098	.080	.082	.068	.056	.048	.040	.033	.015	.013	.011	
4.0	.128	.098	.076	.110	.085	.066	.076	.059	.046	.044	.035	.027	.014	.011	.009	
5.0	.119	.086	.063	.102	.075	.055	.070	.052	.039	.041	.031	.023	.013	.010	.008	
6.0	.110	.077	.053	.095	.066	.046	.065	.047	.032	.038	.027	.019	.012	.009	.006	
7.0	.103	.069	.045	.089	.060	.039	.061	.042	.028	.036	.025	.016	.012	.008	.005	
8.0	.097	.062	.039	.083	.054	.034	.058	.038	.024	.034	.022	.014	.011	.007	.005	
9.0	.091	.057	.034	.079	.049	.029	.055	.035	.021	.032	.021	.012	.010	.007	.004	
10.0	.087	.052	.029	.075	.045	.026	.052	.032	.018	.030	.019	.011	.010	.006	.004	

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2023-12-5

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.54V I:0.0603A P:12.980W PF:0.9759 Freq:50.01Hz Lamp Flux:941.491x1 lm										
NAME: DL3017-WHTC12C02					TYPE:			WEIGHT:		
SPEC.: white RA90 3000K+5000K					DIM.:			SERIAL No.:		
MFR.:					SUR.: 60mm			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	12.4	13.2	12.6	13.3	13.5	12.1	12.9	12.3	13.0	13.2
3H	12.8	13.5	13.0	13.7	13.9	12.5	13.3	12.8	13.5	13.7
4H	12.8	13.5	13.1	13.7	14.0	12.6	13.3	12.9	13.5	13.7
6H	12.8	13.4	13.1	13.7	13.9	12.5	13.2	12.8	13.4	13.7
8H	12.7	13.4	13.0	13.6	13.9	12.5	13.1	12.8	13.4	13.6
12H	12.7	13.3	13.0	13.6	13.8	12.5	13.1	12.8	13.3	13.6
4H 2H	12.4	13.1	12.7	13.4	13.6	12.2	12.9	12.5	13.1	13.3
3H	13.0	13.6	13.3	13.9	14.1	12.8	13.4	13.1	13.7	13.9
4H	13.0	13.6	13.4	13.9	14.2	12.8	13.4	13.2	13.7	14.0
6H	13.0	13.5	13.4	13.8	14.2	12.8	13.3	13.2	13.6	14.0
8H	12.9	13.4	13.3	13.7	14.1	12.7	13.2	13.1	13.5	13.9
12H	12.9	13.3	13.3	13.7	14.1	12.7	13.1	13.1	13.5	13.9
8H 4H	13.0	13.4	13.4	13.8	14.1	12.8	13.2	13.2	13.6	13.9
6H	12.9	13.3	13.3	13.7	14.1	12.7	13.1	13.1	13.5	13.9
8H	12.9	13.2	13.3	13.6	14.1	12.7	13.0	13.1	13.4	13.9
12H	12.8	13.1	13.3	13.5	14.0	12.6	12.9	13.1	13.3	13.8
12H 4H	12.9	13.3	13.3	13.7	14.1	12.7	13.1	13.1	13.5	13.9
6H	12.9	13.2	13.3	13.6	14.1	12.7	13.0	13.1	13.4	13.9
8H	12.8	13.1	13.3	13.5	14.0	12.6	12.9	13.1	13.3	13.8
Variations with the observer position at spacings(CIE Pub.117):										
S = 1.0H	+ 1.8 / - 2.6					+ 1.5 / - 2.4				
1.5H	+ 3.0 / - 2.5					+ 2.7 / - 2.2				
2.0H	+ 2.9 / - 1.4					+ 2.6 / - 1.3				

CIE Pub.117, 941.5 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -0.2)
Area: 0.01131 m2

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2023-12-5

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:220.54V I:0.0603A P:12.980W PF:0.9759 Freq:50.01Hz Lamp Flux:941.491x1 lm		
NAME: DL3017-WHTC12C02	TYPE:	WEIGHT:
SPEC.: white RA90 3000K+5000K	DIM.:	SERIAL No.:
MFR.:	SUR.: 60mm	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	87	81	77	87	80	77	86	80	77	73
0.80	94	89	85	94	88	85	93	88	84	81
1.00	99	93	90	98	93	89	96	93	89	85
1.25	103	98	94	102	97	94	100	96	93	89
1.50	106	101	97	104	100	97	102	99	96	91
2.00	108	104	101	107	103	100	104	101	99	93
2.50	110	106	103	108	105	102	105	103	100	94
3.00	112	108	105	110	107	104	106	104	102	96
4.00	114	111	109	112	109	107	108	106	105	98
5.00	115	113	111	113	111	109	109	107	106	99
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2023-12-5

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:220.54V I:0.0603A P:12.980W PF:0.9759 Freq:50.01Hz Lamp Flux:941.491x1 lm		
NAME: DL3017-WHTC12C02	TYPE:	WEIGHT:
SPEC.: white RA90 3000K+5000K	DIM.:	SERIAL No.:
MFR.:	SUR.: 60mm	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2023-12-5

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

AAI Figure

Test:U:220.54V I:0.0603A P:12.980W PF:0.9759 Freq:50.01Hz Lamp Flux:941.49lx1 lm		
NAME: DL3017-WHTC12C02	TYPE:	WEIGHT:
SPEC.: white RA90 3000K+5000K	DIM.:	SERIAL No.:
MFR.:	SUR.: 60mm	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2023-12-5

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:220.54V I:0.0603A P:12.980W PF:0.9759 Freq:50.01Hz Lamp Flux:941.49lx1 lm		
NAME: DL3017-WHTC12C02	TYPE:	WEIGHT:
SPEC.: white RA90 3000K+5000K	DIM.:	SERIAL No.:
MFR.:	SUR.: 60mm	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2023-12-5

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:220.54V I:0.0603A P:12.980W PF:0.9759 Freq:50.01Hz Lamp Flux:941.491x1 lm		
NAME: DL3017-WHTC12C02	TYPE:	WEIGHT:
SPEC.: white RA90 3000K+5000K	DIM.:	SERIAL No.:
MFR.:	SUR.: 60mm	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	2421
L_0~180(75)av	1097
L_0~180(85)av	182
L_90~270(65)av	2360
L_90~270(75)av	1081
L_90~270(85)av	178
L_45(65)av	2393
L_45(75)av	1085
L_45(85)av	177

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:
 Test Date:2023-12-5

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
 Humidity:65.0%
 Test Distance:7.450m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2023-12-5

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 7.450m [K=1.0000]
Remarks:

```

Range: 0 - 90DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

```