

IP54 LED Surface Mounted Downlight

Product Features

- Quality powder coat finish
- Commercial grade quality and design
- 5 colour selectable 2700K-6500K, Ra > 90
- Easy selectable power 25W, 30W and 36W with an DIP switch on driver
- Made with LM80 certified COB LED chips
- Long life-span with low power consumption
- Include Internal constant current dimmable and flicker free led driver and big terminal block
- IP54 rated, suitable for semi-outdoor applications, such as entrance corridors, awning walkways and enclosed balconies.
- 3 years warranty



3m Pendant Accessories
(Not included)

Technical Specification

Model	DL13618-MW5CTP253036C02	DL13618-MB5CTP253036C02
Watts	25W-30W-36W	
Input Voltage	AC 220~240V 50/60Hz	
LED Chip	COB LED	
Colour Temp.	5-CCT: 2700-3000-4000-5000-6500K	
Lumens Output	3800lm max.	
CRI	Ra > 90	
Beam Angle	60°	
Size	Φ136x180mm	
Power Factor	> 0.9	
Dimmable	Triac dimming, flicker free, C-bus2 compatible	
IP Grade	IP54	
Housing Colour	White	Black
Packing	10PCS/CTN	
Carton Size	48x38.7x20CM	
Warranty	3years	

