


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:230.47V I:0.1544A P:34.749W PF:0.9764 Freq:49.99Hz Lamp Flux:4538.56x1 lm		
NAME: DL3008-WHTC35S03	TYPE:	WEIGHT:
SPEC.: white RA90 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 190mm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 130.61 lm/W			
MODEL	2835 96 5700K	I _{max} (cd)	3642	S/MH(C0/180)	0.96
NOMINAL POWER(W)	35	LOR(%)	100.0	S/MH(C90/270)	0.96
RATED VOLTAGE(V)	220-240	TOTAL FLUX(lm)	4538.6	η UP, DN(C0-180)	0.0, 50.6
NOMINAL FLUX(lm)	4538.56	CIE CLASS	DIRECT	η UP, DN(C180-360)	0.0, 49.4
LAMPS INSIDE	1	η up(%)	0.0	CIBSE SHR NOM	1.00
TEST VOLTAGE(V)	220	η down(%)	100.0	CIBSE SHR MAX	1.05

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2024-09-13

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 7.450m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	3439	3467	3460	3467	3443	3421	3432	3413	0- 10	338.1	338.1	7.45, 7.45
20	2888	2923	2901	2920	2885	2858	2883	2855	10- 20	895.4	1233	27.2, 27.2
30	2129	2152	2110	2137	2109	2080	2119	2093	20- 30	1155	2389	52.6, 52.6
40	1248	1268	1221	1249	1234	1206	1256	1224	30- 40	1043	3432	75.6, 75.6
50	536.1	545.8	518.7	535.6	524.3	513.2	547.3	524.4	40- 50	654.3	4086	90, 90
60	182.9	187.6	176.8	184.4	180.5	174.9	187.5	178.8	50- 60	294.4	4381	96.5, 96.5
70	60.71	62.38	60.24	62.06	60.98	58.60	61.29	58.96	60- 70	106.0	4487	98.9, 98.9
80	22.34	23.52	22.70	23.68	22.56	21.58	22.31	21.05	70- 80	39.72	4526	99.7, 99.7
90	1.262	1.386	1.285	1.502	0.4631	0.4594	0.4477	0.4479	80- 90	12.22	4539	100, 100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25DEG
 Operators:
 Test Date: 2024-09-13

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.428
 Humidity: 65.0%
 Test Distance: 7.450m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:230.47V I:0.1544A P:34.749W PF:0.9764 Freq:49.99Hz Lamp Flux:4538.56x1 lm		
NAME: DL3008-WHTC35S03	TYPE:	WEIGHT:
SPEC.: white RA90 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 190mm	Shielding Angle:



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	4532	4597
80	4539	4612
75	4715	4743
70	6263	6213
65	8406	8221
60	12907	12477
55	19815	19113
50	29427	28471
45	42245	41105


C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2024-09-13

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 7.450m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:230.47V I:0.1544A P:34.749W PF:0.9764 Freq:49.99Hz Lamp Flux:4538.56x1 lm		
NAME: DL3008-WHTC35S03	TYPE:	WEIGHT:
SPEC.: white RA90 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 190mm	Shielding Angle:

ρ_{CC}	80%			70%			50%			30%			10%			0
ρ_W	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Coefficients of Utilization(CU)												
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1.0	1.09	1.06	1.03	1.07	1.04	1.02	1.03	1.01	.99	.99	.97	.96	.96	.94	.93	.91
2.0	.90	.95	.91	.98	.93	.90	.95	.91	.88	.91	.88	.86	.89	.86	.84	.82
3.0	.91	.85	.81	.90	.84	.80	.87	.82	.79	.84	.81	.77	.82	.79	.76	.74
4.0	.84	.77	.72	.83	.76	.72	.80	.75	.71	.78	.74	.70	.76	.72	.69	.67
5.0	.77	.70	.65	.76	.70	.65	.74	.69	.64	.72	.68	.64	.71	.66	.63	.61
6.0	.71	.64	.59	.70	.64	.59	.69	.63	.59	.67	.62	.58	.66	.61	.58	.56
7.0	.66	.59	.54	.65	.59	.54	.64	.58	.54	.63	.57	.53	.61	.57	.53	.51
8.0	.61	.55	.50	.61	.54	.50	.60	.54	.49	.59	.53	.49	.58	.53	.49	.47
9.0	.57	.51	.46	.57	.50	.46	.56	.50	.46	.55	.49	.46	.54	.49	.45	.44
10.0	.54	.47	.43	.53	.47	.43	.52	.47	.43	.52	.46	.42	.51	.46	.42	.41



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2024-09-13

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE G0-2000A_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:230.47V I:0.1544A P:34.749W PF:0.9764 Freq:49.99Hz Lamp Flux:4538.56x1 lm					
NAME: DL3008-WHTC35S03			TYPE:		WEIGHT:
SPEC.: white RA90 3000K+5700K			DIM.:		SERIAL No.:
MFR.:			SUR.: 190mm		Shielding Angle:

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.211	.120	.038	.204	.116	.037	.191	.110	.035	.179	.103	.033	.168	.098	.031	
2.0	.204	.112	.034	.198	.109	.034	.187	.104	.032	.177	.099	.031	.168	.095	.030	
3.0	.194	.103	.031	.189	.101	.031	.180	.097	.030	.171	.094	.029	.163	.090	.028	
4.0	.184	.096	.028	.180	.094	.028	.172	.091	.027	.164	.088	.027	.157	.085	.026	
5.0	.175	.089	.026	.171	.088	.026	.164	.085	.025	.157	.083	.025	.151	.081	.024	
6.0	.166	.083	.024	.163	.082	.024	.156	.080	.023	.150	.078	.023	.145	.076	.023	
7.0	.158	.078	.022	.155	.077	.022	.149	.075	.022	.143	.074	.021	.138	.072	.021	
8.0	.150	.073	.021	.147	.072	.020	.142	.071	.020	.137	.070	.020	.133	.068	.020	
9.0	.143	.069	.019	.140	.068	.019	.136	.067	.019	.131	.066	.019	.127	.065	.019	
10.0	.136	.065	.018	.134	.065	.018	.130	.064	.018	.126	.062	.018	.122	.061	.018	

ρ_{cc}	80%			70%			50%			30%			10%			0	
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
ρ_{fc}	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)										
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020		
1.0	.173	.157	.142	.148	.135	.122	.102	.093	.085	.058	.054	.049	.019	.017	.016		
2.0	.160	.132	.109	.137	.114	.094	.094	.079	.066	.054	.046	.038	.017	.015	.013		
3.0	.150	.114	.085	.129	.098	.074	.088	.068	.052	.051	.040	.030	.016	.013	.010		
4.0	.141	.100	.068	.121	.086	.059	.083	.060	.042	.048	.035	.025	.015	.011	.008		
5.0	.133	.088	.055	.114	.076	.048	.079	.053	.034	.046	.031	.020	.015	.010	.007		
6.0	.126	.079	.046	.108	.069	.040	.075	.048	.028	.043	.028	.017	.014	.009	.006		
7.0	.120	.072	.039	.103	.063	.034	.071	.044	.024	.041	.026	.014	.013	.008	.005		
8.0	.114	.066	.033	.098	.057	.029	.068	.040	.021	.040	.024	.012	.013	.008	.004		
9.0	.109	.061	.029	.094	.053	.025	.065	.037	.018	.038	.022	.011	.012	.007	.004		
10.0	.104	.057	.025	.090	.049	.022	.062	.035	.016	.036	.021	.009	.012	.007	.003		

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2024-09-13

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE G0-2000A_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:230.47V I:0.1544A P:34.749W PF:0.9764 Freq:49.99Hz Lamp Flux:4538.56x1 lm											
NAME: DL3008-WHTC35S03						TYPE:			WEIGHT:		
SPEC.: white RA90 3000K+5700K						DIM.:			SERIAL No.:		
MFR.:						SUR.: 190mm			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	2H	17.0	18.2	17.3	18.3	18.5	16.9	18.1	17.2	18.3	18.4
	3H	17.0	18.1	17.3	18.3	18.5	16.9	18.0	17.2	18.2	18.4
	4H	17.0	18.0	17.3	18.2	18.4	16.9	17.9	17.2	18.1	18.4
	6H	16.9	17.9	17.2	18.1	18.4	16.9	17.8	17.2	18.0	18.3
	8H	16.9	17.8	17.2	18.1	18.3	16.8	17.7	17.2	18.0	18.3
	12H	16.9	17.7	17.2	18.0	18.3	16.8	17.7	17.2	17.9	18.2
4H	2H	16.9	17.9	17.2	18.1	18.4	16.9	17.9	17.2	18.1	18.3
	3H	17.0	17.8	17.3	18.1	18.4	16.9	17.8	17.2	18.0	18.3
	4H	17.0	17.7	17.3	18.0	18.4	16.9	17.7	17.3	18.0	18.3
	6H	17.0	17.6	17.3	18.0	18.3	16.9	17.6	17.3	17.9	18.3
	8H	17.0	17.6	17.4	17.9	18.3	16.9	17.5	17.3	17.9	18.3
	12H	16.9	17.5	17.4	17.9	18.3	16.9	17.5	17.3	17.8	18.2
8H	4H	16.9	17.5	17.3	17.9	18.2	16.8	17.5	17.2	17.8	18.2
	6H	16.9	17.4	17.3	17.8	18.2	16.9	17.4	17.3	17.8	18.2
	8H	16.9	17.4	17.4	17.8	18.2	16.9	17.3	17.3	17.8	18.2
	12H	16.9	17.3	17.4	17.8	18.2	16.9	17.3	17.4	17.7	18.2
12H	4H	16.9	17.4	17.3	17.8	18.2	16.8	17.4	17.2	17.7	18.1
	6H	16.9	17.3	17.3	17.8	18.2	16.8	17.3	17.3	17.7	18.2
	8H	16.9	17.3	17.4	17.7	18.2	16.9	17.3	17.3	17.7	18.2
Variations with the observer position at spacings(CIE Pub.117):											
S = 1.0H	+ 1.6 / - 2.8					+ 1.6 / - 2.9					
1.5H	+ 1.8 / - 2.0					+ 1.8 / - 2.0					
2.0H	+ 3.3 / - 3.4					+ 3.3 / - 3.3					

CIE Pub.117, 4539 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 5.3)
Area: 0.02835 m2

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2024-09-13

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE G0-2000A_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:230.47V I:0.1544A P:34.749W PF:0.9764 Freq:49.99Hz Lamp Flux:4538.56x1 lm		
NAME: DL3008-WHTC35S03	TYPE:	WEIGHT:
SPEC.: white RA90 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 190mm	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	76	68	63	75	67	63	74	67	62	58
0.80	85	77	72	84	77	72	83	76	72	67
1.00	92	84	79	91	84	79	89	84	79	74
1.25	97	90	86	96	90	85	94	88	84	79
1.50	101	94	90	99	94	89	97	92	88	83
2.00	105	99	95	103	98	95	100	96	93	87
2.50	107	102	98	105	101	97	102	98	96	89
3.00	109	105	101	107	103	100	104	101	98	91
4.00	112	108	105	109	106	104	106	103	101	93
5.00	113	110	108	111	108	106	107	105	103	95
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:
 Test Date:2024-09-13

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE G0-2000A_V1 SYSTEM V2.00.428
 Humidity:65.0%
 Test Distance:7.450m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:230.47V I:0.1544A P:34.749W PF:0.9764 Freq:49.99Hz Lamp Flux:4538.56x1 lm		
NAME: DL3008-WHTC35S03	TYPE:	WEIGHT:
SPEC.: white RA90 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 190mm	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2024-09-13

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 7.450m [K=1.0000]
Remarks:

AAI Figure

Test:U:230.47V I:0.1544A P:34.749W PF:0.9764 Freq:49.99Hz Lamp Flux:4538.56x1 lm		
NAME: DL3008-WHTC35S03	TYPE:	WEIGHT:
SPEC.: white RA90 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 190mm	Shielding Angle:

Flux out:2839 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2024-09-13

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE G0-2000A_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:230.47V I:0.1544A P:34.749W PF:0.9764 Freq:49.99Hz Lamp Flux:4538.56x1 lm		
NAME: DL3008-WHTC35S03	TYPE:	WEIGHT:
SPEC.: white RA90 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 190mm	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2024-09-13

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 7.450m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:230.47V I:0.1544A P:34.749W PF:0.9764 Freq:49.99Hz Lamp Flux:4538.56x1 lm		
NAME: DL3008-WHTC35S03	TYPE:	WEIGHT:
SPEC.: white RA90 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 190mm	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	8394
L_0~180(75)av	4739
L_0~180(85)av	4504
L_90~270(65)av	8384
L_90~270(75)av	4760
L_90~270(85)av	4490
L_45(65)av	8358
L_45(75)av	4757
L_45(85)av	4493

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2024-09-13

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE G0-2000A_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25DEG
 Operators:
 Test Date: 2024-09-13

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.428
 Humidity: 65.0%
 Test Distance: 7.450m [K=1.0000]
 Remarks:

```

Range: 0 - 90DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

```