


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:232.07V I:0.0424A P:9.3724W PF:0.9517 Freq:49.99Hz Lamp Flux:414.006x1 lm		
NAME: DL324-BKTC7C02	TYPE:	WEIGHT:
SPEC.: black RA90 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 42mm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 44.17 lm/W			
MODEL	TB1307 3000K	I _{max} (cd)	661.1	S/MH(C0/180)	0.80
NOMINAL POWER(W)	7	LOR(%)	100.0	S/MH(C90/270)	0.75
RATED VOLTAGE(V)	220-240	TOTAL FLUX(lm)	414.01	η UP, DN(C0-180)	0.0, 48.1
NOMINAL FLUX(lm)	414.006	CIE CLASS	DIRECT	η UP, DN(C180-360)	0.0, 51.9
LAMPS INSIDE	1	η up(%)	0.0	CIBSE SHR NOM	0.75
TEST VOLTAGE(V)	220	η down(%)	100.0	CIBSE SHR MAX	0.75

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT: lx)



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2025-07-16

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 7.880m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	556.8	590.5	602.5	573.4	592.5	601.1	575.7	524.9	0- 10	58.12	58.12	14,14
20	371.4	393.2	399.8	417.7	451.2	470.9	420.2	370.4	10- 20	139.6	197.8	47.8,47.8
30	149.3	147.8	159.6	207.4	235.6	226.9	191.0	173.4	20- 30	134.4	332.2	80.2,80.2
40	29.34	31.26	34.53	46.88	57.80	57.00	44.67	36.52	30- 40	62.03	394.2	95.2,95.2
50	6.715	7.714	8.063	9.214	10.83	10.77	8.892	8.076	40- 50	15.53	409.7	99,99
60	0.9811	1.109	1.175	1.248	1.924	1.460	1.305	1.224	50- 60	3.745	413.5	99.9,99.9
70	0.0509	0.0925	0.1199	0.1658	0.1097	0.1421	0.1233	0.1005	60- 70	0.4984	414.0	100,100
80	0	0	0	0	0	0	0	0	70- 80	0.0212	414.0	100,100
90	0	0	0	0	0	0	0	0	80- 90	0	414.0	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT: lm		

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2025-07-16

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.880m [K=1.0000]
Remarks:

LUMINANCE LIMITATION CURVES

Test:U:232.07V I:0.0424A P:9.3724W PF:0.9517 Freq:49.99Hz Lamp Flux:414.006x1 lm		
NAME: DL324-BKTC7C02	TYPE:	WEIGHT:
SPEC.: black RA90 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 42mm	Shielding Angle:



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	0	0
80	0	0
75	0	0
70	107	252
65	565	721
60	1412	1691
55	3673	4522
50	7516	9024
45	13890	16003


C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2025-07-16

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 7.880m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:232.07V I:0.0424A P:9.3724W PF:0.9517 Freq:49.99Hz Lamp Flux:414.006x1 lm		
NAME: DL324-BKTC7C02	TYPE:	WEIGHT:
SPEC.: black RA90 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 42mm	Shielding Angle:

ρ_{CC}	80%			70%			50%			30%			10%			0
ρ_W	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)									
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1.0	1.11	1.09	1.07	1.09	1.07	1.05	1.05	1.04	1.02	1.01	1.00	.99	.98	.97	.96	.94
2.0	1.04	1.01	.97	1.03	.99	.96	.99	.97	.94	.96	.94	.92	.94	.92	.90	.89
3.0	.98	.93	.90	.97	.92	.89	.94	.90	.88	.92	.89	.86	.89	.87	.85	.83
4.0	.92	.87	.83	.91	.86	.83	.89	.85	.82	.87	.84	.81	.85	.82	.80	.78
5.0	.87	.82	.78	.86	.81	.77	.84	.80	.77	.83	.79	.76	.81	.78	.75	.74
6.0	.82	.77	.73	.81	.76	.72	.80	.75	.72	.79	.75	.72	.77	.74	.71	.70
7.0	.78	.72	.68	.77	.72	.68	.76	.71	.68	.75	.71	.68	.74	.70	.67	.66
8.0	.74	.68	.65	.73	.68	.64	.72	.68	.64	.71	.67	.64	.70	.67	.64	.62
9.0	.70	.65	.61	.70	.65	.61	.69	.64	.61	.68	.64	.61	.67	.63	.60	.59
10.0	.67	.62	.58	.66	.61	.58	.66	.61	.58	.65	.61	.58	.64	.60	.57	.56



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2025-07-16

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 7.880m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:232.07V I:0.0424A P:9.3724W PF:0.9517 Freq:49.99Hz Lamp Flux:414.006x1 lm					
NAME: DL324-BKTC7C02			TYPE:		WEIGHT:
SPEC.: black RA90 3000K+5700K			DIM.:		SERIAL No.:
MFR.:			SUR.: 42mm		Shielding Angle:

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.167	.095	.030	.160	.091	.029	.148	.085	.027	.136	.078	.025	.125	.073	.023	
2.0	.159	.087	.027	.153	.084	.026	.143	.079	.025	.133	.075	.023	.124	.070	.022	
3.0	.151	.080	.024	.146	.078	.024	.137	.074	.023	.129	.071	.022	.122	.067	.021	
4.0	.144	.075	.022	.140	.073	.022	.132	.070	.021	.125	.067	.020	.118	.064	.020	
5.0	.137	.070	.020	.133	.069	.020	.127	.066	.019	.121	.064	.019	.115	.061	.018	
6.0	.131	.066	.019	.128	.065	.019	.122	.062	.018	.116	.061	.018	.111	.059	.017	
7.0	.125	.062	.018	.122	.061	.017	.117	.059	.017	.112	.058	.017	.108	.056	.016	
8.0	.120	.059	.016	.117	.058	.016	.113	.056	.016	.109	.055	.016	.105	.054	.016	
9.0	.115	.056	.016	.113	.055	.015	.109	.054	.015	.105	.053	.015	.101	.051	.015	
10.0	.110	.053	.015	.109	.052	.015	.105	.051	.014	.101	.050	.014	.098	.049	.014	

ρcc	80%			70%			50%			30%			10%			0
ρw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.170	.157	.146	.146	.135	.125	.100	.093	.087	.057	.054	.050	.018	.017	.016	
2.0	.155	.133	.114	.132	.114	.099	.091	.079	.069	.052	.046	.040	.017	.015	.013	
3.0	.142	.113	.091	.121	.098	.079	.083	.068	.055	.048	.040	.033	.015	.013	.011	
4.0	.131	.099	.074	.112	.085	.064	.077	.059	.045	.045	.035	.027	.014	.011	.009	
5.0	.122	.087	.061	.105	.075	.053	.072	.053	.038	.042	.031	.022	.013	.010	.007	
6.0	.114	.077	.051	.098	.067	.044	.068	.047	.031	.039	.028	.019	.013	.009	.006	
7.0	.108	.070	.043	.093	.060	.038	.064	.042	.027	.037	.025	.016	.012	.008	.005	
8.0	.102	.063	.037	.088	.055	.032	.061	.039	.023	.035	.023	.014	.011	.007	.005	
9.0	.097	.058	.032	.083	.050	.028	.058	.035	.020	.034	.021	.012	.011	.007	.004	
10.0	.092	.054	.028	.079	.047	.025	.055	.033	.017	.032	.019	.010	.010	.006	.003	

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2025-07-16

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.880m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:232.07V I:0.0424A P:9.3724W PF:0.9517 Freq:49.99Hz Lamp Flux:414.006x1 lm											
NAME: DL324-BKTC7C02					TYPE:			WEIGHT:			
SPEC.: black RA90 3000K+5700K					DIM.:			SERIAL No.:			
MFR.:					SUR.: 42mm			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H		19.0	19.9	19.2	20.0	20.2	19.6	20.5	19.8	20.6	20.8
	3H	18.8	19.6	19.1	19.8	20.0	19.4	20.2	19.7	20.4	20.6
	4H	18.7	19.5	19.0	19.7	19.9	19.3	20.1	19.6	20.3	20.5
	6H	18.7	19.4	18.9	19.6	19.9	19.2	20.0	19.5	20.2	20.4
	8H	18.6	19.3	18.9	19.6	19.8	19.2	19.9	19.5	20.1	20.4
	12H	18.6	19.2	18.9	19.5	19.8	19.1	19.8	19.5	20.1	20.3
4H	2H	18.8	19.5	19.0	19.7	20.0	19.3	20.1	19.6	20.3	20.5
	3H	18.6	19.2	18.9	19.5	19.8	19.2	19.8	19.5	20.1	20.4
	4H	18.5	19.1	18.8	19.4	19.7	19.1	19.7	19.4	20.0	20.3
	6H	18.4	18.9	18.8	19.2	19.6	19.0	19.5	19.3	19.8	20.2
	8H	18.3	18.8	18.7	19.2	19.5	18.9	19.4	19.3	19.8	20.1
	12H	18.3	18.7	18.7	19.1	19.5	18.9	19.3	19.3	19.7	20.1
8H	4H	18.3	18.8	18.7	19.2	19.5	18.9	19.4	19.3	19.8	20.1
	6H	18.2	18.6	18.7	19.0	19.4	18.8	19.2	19.2	19.6	20.0
	8H	18.2	18.5	18.6	18.9	19.4	18.8	19.1	19.2	19.5	20.0
	12H	18.1	18.4	18.6	18.9	19.3	18.7	19.0	19.2	19.4	19.9
12H	4H	18.3	18.7	18.7	19.1	19.5	18.9	19.3	19.3	19.7	20.1
	6H	18.2	18.5	18.6	18.9	19.4	18.8	19.1	19.2	19.5	20.0
	8H	18.1	18.4	18.6	18.9	19.3	18.7	19.0	19.2	19.4	19.9
Variations with the observer position at spacings(CIE Pub.117):											
S = 1.0H	+ 3.5 / -12.0					+ 3.8 / -11.1					
1.5H	+ 5.4 / - 8.1					+ 5.6 / - 8.2					
2.0H	+ 5.7 / -11.5					+ 5.8 / -11.0					

CIE Pub.117, 414.0 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -3.1)
Area: 0.00139 m2

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2025-07-16

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.880m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:232.07V I:0.0424A P:9.3724W PF:0.9517 Freq:49.99Hz Lamp Flux:414.006x1 lm		
NAME: DL324-BKTC7C02	TYPE:	WEIGHT:
SPEC.: black RA90 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 42mm	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	89	82	79	88	82	79	87	82	78	75
0.80	96	90	87	95	90	87	94	89	86	83
1.00	100	95	91	99	94	91	98	94	91	87
1.25	104	99	96	103	99	95	101	97	95	91
1.50	107	102	99	105	101	98	103	100	97	93
2.00	109	105	102	108	104	101	105	102	100	95
2.50	111	107	104	109	106	103	106	103	101	96
3.00	112	109	106	110	108	105	107	105	103	97
4.00	114	111	109	112	110	108	108	107	105	98
5.00	115	113	111	113	111	110	109	108	107	99
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2025-07-16

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.880m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:232.07V I:0.0424A P:9.3724W PF:0.9517 Freq:49.99Hz Lamp Flux:414.006x1 lm		
NAME: DL324-BKTC7C02	TYPE:	WEIGHT:
SPEC.: black RA90 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 42mm	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2025-07-16

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.880m [K=1.0000]
Remarks:

AAI Figure

Test:U:232.07V I:0.0424A P:9.3724W PF:0.9517 Freq:49.99Hz Lamp Flux:414.006x1 lm		
NAME: DL324-BKTC7C02	TYPE:	WEIGHT:
SPEC.: black RA90 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 42mm	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2025-07-16

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.880m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:232.07V I:0.0424A P:9.3724W PF:0.9517 Freq:49.99Hz Lamp Flux:414.006x1 lm		
NAME: DL324-BKTC7C02	TYPE:	WEIGHT:
SPEC.: black RA90 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 42mm	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2025-07-16

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.880m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:232.07V I:0.0424A P:9.3724W PF:0.9517 Freq:49.99Hz Lamp Flux:414.006x1 lm		
NAME: DL324-BKTC7C02	TYPE:	WEIGHT:
SPEC.: black RA90 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 42mm	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	692
L_0~180(75)av	0
L_0~180(85)av	0
L_90~270(65)av	712
L_90~270(75)av	0
L_90~270(85)av	0
L_45(65)av	768
L_45(75)av	13
L_45(85)av	0

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:
 Test Date:2025-07-16

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE G0-2000B_V1 SYSTEM V2.00.428
 Humidity:65.0%
 Test Distance:7.880m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2025-07-16

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE G0-2000B_V1 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 7.880m [K=1.0000]
Remarks:

```

Range: 0 - 90DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.880m [K=1.0000]
Remarks:

```