


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:230.59V I:0.0806A P:17.963W PF:0.9671 Freq:49.99Hz Lamp Flux:1639.45x1 lm		
NAME: LPB3060-WHTC18	TYPE:	WEIGHT:
SPEC.: white RA80 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 555*255mm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 91.27 lm/W
MODEL	2835 3000K	I _{max} (cd)	570.4	S/MH(C0/180)	1.26	
NOMINAL POWER(W)	18	LOR(%)	100.0	S/MH(C90/270)	1.26	
RATED VOLTAGE(V)	220-240	TOTAL FLUX(lm)	1639.5	η UP, DN(C0-180)	0.0, 50.2	
NOMINAL FLUX(lm)	1639.45	CIE CLASS	DIRECT	η UP, DN(C180-360)	0.0, 49.8	
LAMPS INSIDE	1	η up(%)	0.0	CIBSE SHR NOM	1.25	
TEST VOLTAGE(V)	220	η down(%)	100.0	CIBSE SHR MAX	1.35	

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2024-08-13

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 7.450m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	561.0	559.2	557.4	555.6	560.1	558.1	557.0	556.3	0- 10	53.70	53.70	3.28, 3.28
20	532.5	531.1	529.3	526.7	530.8	529.0	528.5	528.2	10- 20	154.0	207.7	12.7, 12.7
30	486.1	485.1	483.3	480.1	483.6	482.1	482.3	482.5	20- 30	234.2	441.9	27, 27
40	422.7	422.9	420.4	417.2	419.8	418.8	419.3	420.4	30- 40	283.5	725.4	44.2, 44.2
50	345.1	345.3	342.8	339.6	341.2	340.9	341.6	343.4	40- 50	295.1	1021	62.2, 62.2
60	255.9	256.0	254.2	249.9	251.0	250.7	252.8	254.4	50- 60	266.9	1287	78.5, 78.5
70	159.9	160.2	159.8	154.2	153.9	154.2	158.2	159.0	60- 70	203.3	1491	90.9, 90.9
80	68.45	68.69	69.65	63.59	62.60	62.88	67.74	67.52	70- 80	117.0	1608	98.1, 98.1
90	2.046	2.000	1.648	1.231	0.5713	0.6061	0.7412	1.652	80- 90	31.73	1639	100, 100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25DEG
 Operators:
 Test Date: 2024-08-13

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.428
 Humidity: 65.0%
 Test Distance: 7.450m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:230.59V I:0.0806A P:17.963W PF:0.9671 Freq:49.99Hz Lamp Flux:1639.45x1 lm		
NAME: LPB3060-WHTC18	TYPE:	WEIGHT:
SPEC.: white RA80 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 555*255mm	Shielding Angle:



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	2406	2445
80	2785	2834
75	3078	3098
70	3304	3302
65	3479	3463
60	3616	3592
55	3717	3692
50	3793	3768
45	3854	3831


C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2024-08-13

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 7.450m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:230.59V I:0.0806A P:17.963W PF:0.9671 Freq:49.99Hz Lamp Flux:1639.45x1 lm		
NAME: LPB3060-WHTC18	TYPE:	WEIGHT:
SPEC.: white RA80 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 555*255mm	Shielding Angle:

ρ_{CC}	80%			70%			50%			30%			10%			0
ρ_W	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Coefficients of Utilization(CU)												
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1.0	1.04	.99	.96	1.02	.98	.94	.97	.94	.91	.93	.91	.88	.90	.88	.86	.83
2.0	.90	.83	.78	.88	.82	.77	.85	.79	.75	.82	.77	.73	.79	.75	.72	.69
3.0	.79	.71	.64	.78	.70	.64	.75	.68	.63	.72	.66	.62	.69	.65	.60	.58
4.0	.70	.61	.54	.69	.60	.54	.66	.59	.53	.64	.58	.53	.62	.56	.52	.50
5.0	.63	.53	.47	.61	.53	.47	.59	.52	.46	.57	.51	.45	.55	.50	.45	.43
6.0	.56	.47	.41	.55	.47	.41	.53	.46	.40	.52	.45	.40	.50	.44	.39	.37
7.0	.51	.42	.36	.50	.42	.36	.49	.41	.36	.47	.40	.35	.46	.40	.35	.33
8.0	.46	.38	.32	.46	.38	.32	.44	.37	.32	.43	.36	.32	.42	.36	.31	.29
9.0	.43	.34	.29	.42	.34	.29	.41	.34	.29	.40	.33	.28	.39	.33	.28	.26
10.0	.39	.31	.26	.39	.31	.26	.38	.31	.26	.37	.30	.26	.36	.30	.26	.24



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2024-08-13

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 7.450m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:230.59V I:0.0806A P:17.963W PF:0.9671 Freq:49.99Hz Lamp Flux:1639.45x1 lm					
NAME: LPB3060-WHTC18			TYPE:		WEIGHT:
SPEC.: white RA80 3000K+5700K			DIM.:		SERIAL No.:
MFR.:			SUR.: 555*255mm		Shielding Angle:

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.311	.177	.056	.304	.174	.055	.291	.167	.053	.279	.161	.052	.268	.155	.050	
2.0	.293	.161	.049	.287	.158	.049	.275	.153	.048	.264	.148	.046	.254	.144	.045	
3.0	.271	.144	.043	.266	.142	.043	.255	.138	.042	.246	.135	.041	.237	.131	.041	
4.0	.250	.130	.038	.245	.128	.038	.236	.125	.037	.227	.122	.037	.220	.119	.036	
5.0	.231	.118	.034	.227	.116	.034	.219	.114	.034	.211	.111	.033	.204	.109	.033	
6.0	.214	.107	.031	.210	.106	.031	.203	.104	.030	.196	.102	.030	.190	.100	.030	
7.0	.199	.099	.028	.196	.098	.028	.189	.096	.028	.183	.094	.027	.178	.092	.027	
8.0	.186	.091	.026	.183	.090	.025	.177	.089	.025	.172	.087	.025	.167	.086	.025	
9.0	.174	.084	.024	.172	.084	.023	.166	.082	.023	.162	.081	.023	.157	.080	.023	
10.0	.164	.079	.022	.162	.078	.022	.157	.077	.022	.152	.076	.022	.148	.075	.021	

ρcc	80%			70%			50%			30%			10%			0
ρw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.180	.156	.134	.154	.134	.116	.106	.092	.080	.061	.053	.046	.019	.017	.015	
2.0	.172	.132	.098	.148	.114	.085	.101	.079	.059	.058	.046	.035	.019	.015	.011	
3.0	.165	.114	.074	.141	.099	.064	.097	.069	.045	.056	.040	.027	.018	.013	.009	
4.0	.157	.101	.058	.135	.087	.051	.093	.061	.036	.054	.036	.021	.017	.012	.007	
5.0	.150	.091	.047	.129	.078	.041	.089	.055	.029	.051	.032	.017	.017	.010	.006	
6.0	.142	.082	.039	.122	.071	.034	.084	.050	.024	.049	.029	.014	.016	.010	.005	
7.0	.136	.075	.033	.117	.065	.029	.081	.046	.020	.047	.027	.012	.015	.009	.004	
8.0	.129	.070	.029	.111	.060	.025	.077	.042	.018	.045	.025	.011	.014	.008	.003	
9.0	.123	.065	.025	.106	.056	.022	.073	.039	.016	.043	.023	.009	.014	.008	.003	
10.0	.117	.060	.022	.101	.052	.020	.070	.037	.014	.041	.022	.008	.013	.007	.003	

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2024-08-13

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE G0-2000A_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:230.59V I:0.0806A P:17.963W PF:0.9671 Freq:49.99Hz Lamp Flux:1639.45x1 lm											
NAME: LPB3060-WHTC18					TYPE:			WEIGHT:			
SPEC.: white RA80 3000K+5700K					DIM.:			SERIAL No.:			
MFR.:					SUR.: 555*255mm			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	15.8	17.3	16.1	17.5	17.7	15.8	17.3	16.0	17.5	17.7	
	3H	17.3	18.7	17.6	19.0	19.2	17.3	18.7	17.6	18.9	19.2
	4H	17.9	19.3	18.2	19.5	19.8	17.9	19.3	18.2	19.5	19.8
	6H	18.4	19.6	18.7	19.9	20.2	18.4	19.6	18.7	19.9	20.2
	8H	18.5	19.7	18.9	20.0	20.3	18.5	19.8	18.9	20.0	20.3
	12H	18.6	19.8	18.9	20.1	20.4	18.6	19.8	19.0	20.1	20.4
4H	2H	16.4	17.7	16.7	18.0	18.3	16.4	17.7	16.7	18.0	18.2
	3H	18.1	19.3	18.5	19.6	19.9	18.1	19.3	18.5	19.6	19.9
	4H	18.9	19.9	19.2	20.3	20.6	18.9	19.9	19.2	20.3	20.6
	6H	19.4	20.4	19.8	20.7	21.1	19.4	20.4	19.8	20.8	21.1
	8H	19.6	20.5	20.0	20.9	21.3	19.7	20.5	20.1	20.9	21.3
	12H	19.8	20.6	20.2	21.0	21.4	19.8	20.6	20.2	21.0	21.4
8H	4H	19.1	20.0	19.5	20.4	20.8	19.1	20.0	19.6	20.4	20.8
	6H	19.9	20.6	20.3	21.0	21.4	19.9	20.6	20.3	21.0	21.5
	8H	20.1	20.8	20.6	21.2	21.7	20.2	20.8	20.6	21.3	21.7
	12H	20.3	20.9	20.8	21.4	21.8	20.4	21.0	20.9	21.4	21.9
12H	4H	19.1	20.0	19.6	20.4	20.8	19.2	20.0	19.6	20.4	20.8
	6H	19.9	20.6	20.4	21.0	21.5	19.9	20.6	20.4	21.0	21.5
	8H	20.2	20.8	20.7	21.2	21.7	20.3	20.8	20.7	21.3	21.8
Variations with the observer position at spacings(CIE Pub.117):											
S = 1.0H	+ 0.2 / - 0.2					+ 0.2 / - 0.2					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.1 / - 0.3					+ 0.1 / - 0.3					

CIE Pub.117, 1639 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 1.7)
Area: 0.141525 m2

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2024-08-13

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE G0-2000A_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:230.59V I:0.0806A P:17.963W PF:0.9671 Freq:49.99Hz Lamp Flux:1639.45x1 lm		
NAME: LPB3060-WHTC18	TYPE:	WEIGHT:
SPEC.: white RA80 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 555*255mm	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	57	46	39	57	45	39	55	45	38	32
0.80	67	56	48	66	55	48	65	54	48	41
1.00	76	65	57	75	64	57	72	65	56	49
1.25	83	72	65	81	72	65	79	70	64	57
1.50	88	78	71	86	77	70	83	75	69	62
2.00	95	86	80	93	85	79	89	83	77	70
2.50	99	91	85	97	90	84	93	87	82	74
3.00	102	95	90	100	94	89	96	91	86	78
4.00	106	100	96	104	99	94	100	95	92	83
5.00	109	104	100	106	102	98	102	98	95	86
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2024-08-13

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE G0-2000A_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:230.59V I:0.0806A P:17.963W PF:0.9671 Freq:49.99Hz Lamp Flux:1639.45x1 lm		
NAME: LPB3060-WHTC18	TYPE:	WEIGHT:
SPEC.: white RA80 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 555*255mm	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2024-08-13

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE G0-2000A_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

AAI Figure

Test:U:230.59V I:0.0806A P:17.963W PF:0.9671 Freq:49.99Hz Lamp Flux:1639.45x1 lm		
NAME: LPB3060-WHTC18	TYPE:	WEIGHT:
SPEC.: white RA80 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 555*255mm	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2024-08-13

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE G0-2000A_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:230.59V I:0.0806A P:17.963W PF:0.9671 Freq:49.99Hz Lamp Flux:1639.45x1 lm		
NAME: LPB3060-WHTC18	TYPE:	WEIGHT:
SPEC.: white RA80 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 555*255mm	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators:
Test Date: 2024-08-13

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 7.450m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:230.59V I:0.0806A P:17.963W PF:0.9671 Freq:49.99Hz Lamp Flux:1639.45x1 lm		
NAME: LPB3060-WHTC18	TYPE:	WEIGHT:
SPEC.: white RA80 3000K+5700K	DIM.:	SERIAL No.:
MFR.:	SUR.: 555*255mm	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	3434
L_0~180(75)av	2993
L_0~180(85)av	2206
L_90~270(65)av	3450
L_90~270(75)av	3073
L_90~270(85)av	2370
L_45(65)av	3427
L_45(75)av	3001
L_45(85)av	2127

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:
Test Date:2024-08-13

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE G0-2000A_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25DEG
 Operators:
 Test Date: 2024-08-13

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE G0-2000A_V1 SYSTEM V2.00.428
 Humidity: 65.0%
 Test Distance: 7.450m [K=1.0000]
 Remarks:

```

Range: 0 - 90DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:7.450m [K=1.0000]
Remarks:

```